

ELECTRONIC PROJECTION SYSTEMS



3M™ Multimedia Projector MP8625

The Full-featured, Ultra-portable Solution

You don't have to sacrifice brightness and multimedia muscle for mobility with this **all-star presentation performer**. Combining **superior portability** (only 11 lbs.) with a **rich feature set**, the 3M™ Multimedia Projector MP8625 packs plenty of power and functionality for the conference room and looks brilliant in highly mobile situations.



Sharp SVGA resolution, 700 ANSI lumens of full-color brightness and built-in stereo speakers make your ideas look and sound impressive.

Intelligent image scaling technology optimizes image quality for XGA and VGA resolutions and improves video performance. Four input channels support the simultaneous connection of two computers and two video signals, providing **complete multimedia connectivity**. The



VirtualMouse remote control gives you **fingertip command** of your presentation from anywhere in the room. Offering the perfect combination of functionality and portability, the 3M MP8625 is the ideal companion for mobile professionals.

Make the meeting.



KEY FEATURES

- 700 ANSI lumens of on-screen brightness
- Active-matrix TFT LCD technology with 16.7 million colors at true SVGA (800 x 600) resolution
- Compact lightweight design without sacrificing brightness and image quality
- Intelligent image scaling technology optimizes image quality for XGA and VGA resolution and video
- VirtualMouse remote control with laser pointer
- Manual zoom and manual focus
- Digital image magnification
- Four input channels for the simultaneous connection of two computers and two video signals
- Monitor loop-through lets you view an external monitor and your projected image simultaneously
- Kensington® Security Slot for protection from theft (Kensington Microsaver needed)
- Built-in stereo speakers and audio output that allow you to hook up external speakers

Computer Compatibility:

- PC-compatible — XGA, SVGA, VGA
- Apple® Macintosh® (II, LC, Quadra, Power Macintosh and PowerBook®)

Video Compatibility:

- NTSC, PAL, SECAM, PAL-M, PAL- (BGDHI)

Accessories Included:

- Detachable power cords
- VGA (RGB) cable, Mac adapter
- RCA video cable, S-video cable, dual RCA audio cable
- Serial, ADB, PS/2® mouse cables
- Remote control with discpad and laser pointer (with batteries)
- Stereo mini-jack
- Seven language operator's guide

3M™ Multimedia Projector MP8625

TECHNICAL SPECIFICATIONS

- LCD type: 0.9" Active-matrix TFT (x3)
- Resolution: 800 W x 600 H pixels (SVGA)
- Brightness: 700 ANSI lumens
- Colors: 16.7 million (maximum)
- Contrast ratio: 100:1 ANSI (200:1peak)
- Aspect ratio: 4:3
- Zoom lens: Manual 1:1.3
- Screen size: 21" (minimum) to 240" (maximum) diagonal
- Horizontal scan: 25-60 kHz
- Vertical scan: 56-85 Hz
- Input terminals:
 - S-Video: (2) mini DIN 4-pin
 - Video: (2) RCA jack
 - Audio: (2) RCA jack
 - RGB: (2) mini D-sub 15-pin
 - Audio: (2) stereo mini jack
- Output terminals:
 - Audio: (1) stereo mini jack
 - RGB: (1) mini D-sub 15-pin (female)
 - Mouse control and RS-232C: (1) mini D-sub 15-pin (male)
- Lamp type: 120-watt UHP
- Lamp life: 2,000 hours
- Dimensions: 9.4" (23.9cm) W x 4.9" (12.5 cm) H x 13.3" (33.7 cm) L
- Speakers: 2 x 1 watt
- Weight: 11 lbs. (5 kg)
- Operating temperature: 32°F (0°C) to 95°F (35°C)
- Storage temperature: -4°F (-20°C) to 140°F (60°C)
- Power consumption: 230 watts (maximum)
- Power supply: AC 100-120V, AC 200-240V
- Regulatory approvals: FCC Part 15 Class A, UL, cUL
- Warranty: Two-year limited warranty on parts and labor. See warranty for details. Lamp: 90 days or 180 hours, whichever comes first.

Optional Accessories

- Hard (ATA) cover shipping case: 78-6969-8584-1
- Soft cover carry case: 78-6969-8585-8
- User replaceable lamp kit: 78-6969-8583-3
- Ceiling mount: 78-6969-8748-2
- Object display camera: 78-6969-8578-3
- Monitor Splitter box kiy: XX-0034-1736-5

1-800-328-1371

www.3M.com/meetings



3M Visual Systems Division

Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada

P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico



Recycled paper,
40% pre-consumer,
10% post-consumer

Litho in U.S.A. © 3M 1998
78-6970-7826-5 (09840.0)LP

Specifications subject to change without notice.

Kensington is a registered trademark of Kensington Technology Group. Apple, Macintosh, Mac and PowerBook are registered trademarks of Apple Computer, Inc. PS/2 is a registered trademark of IBM Corp. RCA is a trademark of Radio Corporation of America.