


IBM iLV300

IBM iLV300



Display Type	 1 Chip DLP SVGA 4/3 Ti Digital Light Processing Chip	
Ansi-Lumen	-	Lux (bei 203 cm Screen)
Contrast	2000:1 full on/off	-
Black Level	-	-
Offset	-	-
Resolution	SVGA 800 x 600 480.000 Pixel XGA 1024 x 768 compressed	
Video Modes	1080i/720p HDTV NTSC, PAL, SECAM, PAL-N und PAL-M	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Very narrow picture width and rooms with very little light.	
Light Source	- Lamp	
Light Life	Articel Nr.: 31P9870 3000 h.	
Operating Costs	-	
Focus	Manual	
Zoom	Manual	
Objective	-	
Throw Ratio	-	
Audio	2,5W Mono	
Connections	Cinch Video in S-Video in D-sub 15pin in	
Ceiling Mounting	Yes	
Power	-	
Size WxHxD	-	
Operating Noise	35dB	
Weight	-	
Keystone	-	
Illumination	-	
Frequenz	-	

Foot-Lamberts	-
	-
Features	■ Blank (Black screen button) ■ Remote control with laser pointer ■ Overscan adjustable
	Bulb only NLMP1855
	Lamp ruby Ruby-LMP1855
Optional	Lamp original 31P9870
	Compatible lamp LMP-K1855
Status	Order here: https://www.hcinema.de/lampen/shop-en.php?id=n1855 - Discontinued (EOL) // Last update of the data: 2023-08-04



More Details



HCinema

<https://www.projector-database.com/pro/IBMiLV300-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.