

P3251 PROJECTOR


DLP Technology – Ultra lightweight

Weighing only 1.2 kg (2.7lbs), the P3251 projector is an ultra-lightweight powerhouse casting 2100 ANSI Lumens brightness, and boasting native XGA (1024 x 768) resolution and 3700:1 contrast ratio for high-impact projection in presentation venues of different sizes.

An HDMI port delivers uncompressed digital signals and multi-channel audio, offering easy connectivity to HD-quality broadcasts.

Why P3251 Projector?

- Resolution Native XGA (1,024 x 768)
Maximum UXGA (1,600 x 1,200),
1080p (1,920 x 1,080)
- Contrast Ratio 3700:1
- Brightness 2100 ANSI Lumens
(Standard), 1,575 ANSI Lumens
(ECO)
- Weight 1.2 kg (2.7lbs)
- USB and SD Card Reader



Technical Specification

Model Name	P3251 DLP® 3D Ready
Resolution	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	3700:1
Displayable Colours	1.07 Billion Colours
Brightness	2,100 ANSI Lumens (Standard), 1,575 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal Scan Rate	30 ~ 100 kHz
Vertical Scan Rate	50 ~ 120 Hz
Lamp Type / Life	Osram 165 W user replaceable P-VIP lamp 3,500 Hours (Standard), 5,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	N/A
Audio	One Internal Speaker with 1 watt Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	209 Watts (Operation), <1 Watt (Standby)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	36 dBA (Standard mode), 29 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, HDMI (Video, Audio, HDCP) x 1, PC Audio (Stereo mini jack) x 1, USB (Type A) x 1, SD (SDHC) x 1
Control Interface	USB (Type B) x 1
Weight and Dimensions	2.7 lbs (1.2 Kg), 210 x 165 x 64 mm (8.3" x 6.5" x 2.5")
Compliance	C-Tick (AS/NZS 60950)
Standard Accessories	AC power cord, VGA cable, Composite video cable, Remote control, Battery for remote control, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.

¹ Specifications vary depending on model.