

P5270 PROJECTOR

DLP Technology – Professional Series

The impressive P5270 combines mobility and superior performance, enabling you to deliver your visions without compromise. The P5270 has the right features for Education, training, meeting and small conference rooms.



The Acer P5270 projects ultra bright image, visible on a screen up to 12m away.

Why P5270 Projector?

- Resolution Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
- Contrast Ratio 2000:1
- Brightness 3,000 ANSI Lumens (Standard), 2,400 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) to 39.0' (11.9m)



2000:1



Technical Specifications

Model Name	P5270
Resolution	Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p) (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2000:1
Displayable Colours	134 Million Colors
Brightness	3,000 ANSI Lumens (Standard), 2,400 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Lamp Life	3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 3 watts Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	280 Watts (Operation), 10 Watts (Standby)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	31 dBA (Standard mode), 28 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 2
Output Interface	Analog RGB (D-sub) x 1
Computer Interface	USB (Type B) x 1, RS232 (Mini DIN) x 1
Weight and Dimensions	6.6 lbs (3.0Kg) 299 x 229 x 93 mm (11.8" x 9.0" x 3.7")
Compliance	C-Tick (AS/NZS 60950)
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.

¹ Specifications vary depending on model.