Asee ATP 3650



Brief Introduction

Display Type

Ansi-Lumen

Contrast Black Level

Offset

Beta 2.5

The standard portable ATP 3650 LCD has 3000 Ansi lumens, a contrast of 600:1 and an XGA 1024 x 768 resolution. The projector can illuminate a picture width of up to 477 cm with its 3000 Ansi lumens. In room light, however, the image width should ideally be less than 318 cm. It is no longer offered by the manufacturer Asee.

ω1000 Lux (bei 200 cm Screen)
600:1 full on/off
1,675 min. Lumen

XGA 4/3 Liquid Crystal Display

3000

600:1 full on/off

5,0000 min. Lumen

0,9" LCD TFT Panel

Resolution

XGA 1024 x 768 786.432 Pixel

Video Modes PAL, SECAM, NTSC,

Standard-Portabel | External training and company presentations, as well as product

Application

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source 250W SHP Lamp

Light Life

Operating Costs

Focus Manual

Zoom Manual 1,18

Objective F=1,7-2,0

Throw Ratio

Audio

D-sub 15pin in

YUV in

Connections Cinch Video in

S-Video in

Ceiling Mounting

320W Power

270 x 120 x 350 mm (10,6"x4,7"x13,8") 11,34 L/dm³ Size WxHxD

Operating Noise

4,50 kg / 8,82 lbs. Weight Vert.: +/-15° Keystone


H-sync: 13-80 kHz Frequenz V-sync: 50-85 Hz

93 fL / max. 477 cm screen width

Features

Status

Data



Illumination

Foot-Lamberts

319 cd/m²

- Discontinued (EOL) // Last update of the data: 2023-09-12

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.