## **Barco HDF W26**





**Brief Introduction** Beta 2.5

The Barco model HDF W26 is a DLP projector with WUXGA 1920 x 1200 resolution and a contrast of 2600:1. The built-in lens shift function provides freedom when setting up. The projector will be able to illuminate an image width of 1541 cm well. Rooms with residual light can be created by the projector with a smaller image width, max. 1027 cm is recommended here. In the event that the image is still too small, the projector offers integrated edge blending software, with which several projectors can project a large image together. On the market since 2012, the model is no longer offered by the manufacturer Barco. 3 x 0,96" DLP Chip

Display Type

Ansi-Lumen

Contrast Black Level

Lens shift

Video Modes

Light Source

Light Life

WUXGA 16/9 Ti Digital Light Processing Chip

23000 / 26000 Center lumens

2600:1 full on/off 8,8462 min. Lumen

Vert.: +55% -5% Hori.: +/-15%

WUXGA 1920 x 1200 Resolution 2.304.000 Pixel

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Event | Very large screen width and rooms with plenty of light and shaded daylight. Application

3.8KW Xenon Lamp

Articel Nr.: R9854537 / R9854420

750 h.

**Operating Costs** 

Powered **Focus** 

Zoom Powered

Objective optional

Throw Ratio optional

Audio No

> **DVI mit HDCP** 3G HDSDI/SDI weitere optional

Ceiling Mounting Yes Power 4550W

Size WxHxD 707 x 548 x 1025 mm (27,8"x21,6"x40,4") 397,12 L/dm<sup>3</sup>

Operating Noise 60dB

Lux:10222 Lux Room light max.: 2044 Lux Candela pro m<sup>2</sup>:3255 cd/m<sup>2</sup> 62 cm Foot-Lamberts:950 fL 16/9 screen width:200 cm Screen:1 Gain


Shift: 62 cm

Weight

Connections

99,00 kg / 218,26 lbs.

■ Control via web browser



■ Lan network compatible.

Refurbished lamp original R9854538 / R9854536 / R9854541

Optional Lamp original R9854537 / R9854535 / R9854540

Order here: https://www.hcinema.de/lampen/shop-en.php?id=22415

## **Optional Lenses**

Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
TLD (7.5 ~ 11.5:1)	7.5-11.5:1	15-23 m	55-5%	+/-15%	Powered
TLD (4.5 ~ 7.5:1)	4.5-7.5:1	9-15 m	55-5%	+/-15%	Powered
TLD (2.8 ~ 4.5:1)	2.8-4.5:1	5.6-9 m	55-5%	+/-15%	Powered
TLD (2.0 ~ 2.8:1)	2-2.8:1	4-5.6 m	55-5%	+/-15%	Powered
TLD (1.5 ~ 2.0:1)	1.5-2:1	3-4 m	55-5%	+/-15%	Powered
Fix Optional Lenses					
TLD (1.2:1)	1.2:1	2.4 m			No Zoom
TLD (0.73:1)	0.73:1	1.5 m			No Zoom
Status 2012 Discontinued (FOL) //Lest undete of the data; 2024 07 04					

Status 2012 Discontinued (EOL) // Last update of the data: 2024-07-04

Data









More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.