## Bauer VP 2000





**Brief Introduction** 

Beta 2.5

The VP 2000 LCD has 400 Ansi lumens, a contrast of 100:1 and a resolution. The projector can illuminate a picture width of up to 174 cm well thanks to the 400 Ansi lumens. In room light, however, the image width should ideally be less than 116 cm. This model is no longer offered by Bauer.

Display Type

3 x LCD TFT Panel

3x 4/3 Liquid Crystal Display

Ansi-Lumen Contrast Black Level

Video Modes

400 100:1 full on/off 4,0000 min. Lumen

100:1 full on/off 1.33 min. Lumen

Offset Resolution

3 x 100980 Pixel NTSC, PAL, SECAM

Stationär | Permanent installation in the training room and meeting room as well as the

Application conference room.

Very narrow picture width and rooms with very little light.

150W Metalldampflampe Light Source Articel Nr.: LMPf14740

Light Life 2000 h.

**Operating Costs** 

**Focus** Manual

Zoom Manual 1,83

Objective F=4,5 f=145-265 mm

Throw Ratio

Audio

Connections

S-Video: (1) Mini DIN 4-pin Video: (1) RCA jack

Scart in

Ceiling Mounting

220W Power

251 x 253 x 618 mm (9,9"x10"x24,3") 39,24 L/dm3 Size WxHxD

**Operating Noise** 

Weight 14,00 kg / 30,86 lbs. Keystone

Illumination

Frequenz


Foot-Lamberts 12 fL / max. 174 cm screen width

41 cd/m<sup>2</sup>

**Features** 

Status Data

- Discontinued (EOL) // Last update of the data: 2023-08-04



## More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.