## **BeamBox Evolution R 1**







**Brief Introduction** 

a VGA 640 x 480 resolution. The manufacturer BeamBox specifies a service life of 30,000 hours, which is over 20.5 years if enjoyed for four hours a day. Thanks to the built-in rechargeable battery, the projector does not require a power supply for 1 hour, allowing it to be set up spontaneously and easily anywhere. It was launched in 2009 and is no longer offered by the manufacturer BeamBox. Lcos Panel

on 10 Lux (bei 200 cm Screen)
on 200:1 full on/off
on 0,051 min. Lumen

Display Type

Contrast

Light Life

Black Level

VGA 4/3 Liquid Crystal on Silicon (LCOS)

Ansi-Lumen

30 200:1 full on/off 0,1500 min. Lumen

Offset

VGA 640 x 480 Resolution 307.200 Pixel

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p Game-Portabel | Very portable, small-screen projections. Application Very narrow picture width and rooms with very little light.

Light Source LED 30000 h.

**Operating Costs** 0.00 € LED

Focus Manual

No Zoom Zoom

Objective

Throw Ratio

Audio 1W Mono

Connections Ceiling Mounting Power

Size WxHxD 59 x 28 x 108 mm (2,3"x1,1"x4,3") 0,18 L/dm<sup>3</sup>

**Operating Noise** 

Lux:10 Lux Room light max.:2 Lux Candela pro m<sup>2</sup>:3 cd/m<sup>2</sup> Foot-Lamberts:1 fL 4/3 screen width:200 cm Screen:1 Gain

Weight

0,175 kg / 0 lbs.

VOLUTIO

Keystone Illumination

Frequenz

Foot-Lamberts

1 fL / max. 48 cm screen width

 $3 \text{ cd/m}^2$ 

Features

■ 1 Std.

Status

2009 Discontinued (EOL) // Last update of the data: 2023-09-20

Data









Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.