
BenQ MW516

Digital Projector



Freephone 080

















Disales Technol	D1081	. ®				
Display Technology	DLP® by Texas Instruments®					
Native Resolution	WXGA (1280 x 800)					
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)					
Brightness	2800 ANSI Lumens					
Contrast Ratio	10,000:1 (Full on / Full off)					
mage Size	30" to 300"					
Throw Ratio	1.46 to 1.60 (62" @ 2 meter)					
Zoom Ratio	Manual Zoom, 1.20:1					
Projection Offset	120% ±5%					
Keystone correction	ID, vertical +/- 40 degrees					
Lens	F = 2.55 ~ 3.06, f = 21 ~ 25.6 mm					
Lamp Life*	190W, 4500 / 6000 / 6500 hours (Normal / Economic / SmartEco mode)					
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first					
Operational Noise	29 / 27 dB (Normal / Economic mode)					
Displayable Colours	Full 1.07 billion color palette					
Aspect Ratio	16:10 Native, 5 aspect ratio selectable					
Horizontal Frequency	31 ~ 90 kHz					
Vertical Scan Rate	50 ~ 120 Hz					
Interface	Computer in (D-sub 15pin) x 2		Audio in (Mini Jack) × I			
	(shared with Component) Audio out (Mini Jack) x		Audio out (Mini Jack) x I			
	Monitor out (D-sub 15pin) x I		Speaker 2W x I			
	HDMI vI.3 xI		USB (Type B) x I (Download & Page up/down)			
	Composite Video in (RCA) x I RS232 (DB-9pin) x I					
	S-Video in (Mini DIN 4pin) x I					
Compatibility	Video Compatibility NTSC / PAL / SECAM					
	HDTV Compatibility 480i / 480p / 576i / 576p / 720p / 1080i / 1080p PC: 120Hz Frame Sequential 3D for resolutions up to WXGA 3D Compatibility PC: 60Hz Top-bottom 3D for resolutions up to SXGA+					
				Video: 60Hz Frame Sequential 3D for resolutions up to 480i		
				Dimensions (HxWxD)	124 x 302 x 232.7 mm	ı
	Weight	Net weight: 2.5 kg. Gross weight: 3.5 kg.				
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz					
	Normal mode: 245W, Standby < 1W					
Power consumption	SmartEco mode: I20W (will vary depending on the projected content)					
On Screen Display Languages	Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek /					
	Hindi / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romania					
	/ Russian / Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese / Turkish (28 Languages)					
Application Modes	Dynamic / sRGB / Pres	entation / Cinema / Us	ser I / User 2			
Functions	SmartEco		Instant Restart			
	BrilliantColor™		Quick Auto Search			
	Closed Captioning		Wall Color Correction			
	3D Color Management		Freeze + blank			
	Digital Zoom (x2)		Auto Off			
	HDTV Compatible		Security Password			
	Windows 7 Certified		Security Bar + K-locker slot			
	High Altitude Mode		Presentation Timer			
	Quick Start Guide		VGA Cable			
Accessories Included						
	Manual CD Power Cord					
	Remote Control w/batt	ery				
Accessories Optional	Presentation Plus		Spare Lamp Kit			
	RS232 Cable		Ceiling mount			
	3D Glasses		Soft Carry Case			

^{*} Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.



