



DESIGNED FOR EDUCATION | **MW881UST**
Future Proof • Excellent Image Quality • Affordable



Features

- Native WXGA (1280 x 800) Resolution
- 2500 ANSI Lumens, 5000:1 Contrast Ratio
- 0.24 Ultra Short-Throw Ratio
- LAN Control/Display, UBS Reader/Display
- Wireless Display (Optional), 20W Speaker

Top / Front View



Top



Front

Input and Output Terminals

Back



- 12V Trigger x1
- RS-232 x1
- RGB Output x1
- RGB In/Component x2
- USB Type A & Mini B
- RJ45 x1 (Control/Display)
- S-Video / Video x1
- Audio R/L x1
- Audio In & Out / Mic-In



SNMP



10W Speaker x2

Specifications

EDUCATION

Native Resolution	WXGA (1280 x 800)
Brightness	2500 ANSI Lumens
Contrast Ratio	5000:1 (Full on/Full off)
Keystone	Manual Vertical +/- 15°
Aspect Ratio	Native 16:10 (5 Aspect Ratio Selectable)
Zoom Ratio	Fixed
Color	Full 1.07 Billion colors palett
Image Size (Diagonal)	57" - 300"
Throw Ratio	0.24 (92" @ 1.7 Feet)
Lamp Life	230W, 3500/5000 hours (Normal/Economical Mode)
PC Compatibility	VGA (640 x 480) to UXGA (1600 x 1200)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	31-99 kHz
Vertical Scan Rate	48-120 Hz
Input Terminals PC/AV	Analog RGB/Component: D-Sub 15 Pin x2 LAN Networking: RJ45 x1 (LAN Display) USB (Type A) x1 (Reader) USB Type Mini-B x1 (Display) S-Video: Mini Din 4 Pin x1 Composite Video: RCA x1 Microphone-In: Min-Jack x1 Audio L/R: RCA x2 Stereo Mini-Jack x1
Output Terminals PC/AV	Analog RGB: D-Sub 15 Pin x1 Variable Audio Out: Stereo Mini-Jack x1 Speaker: 10W x2, 12V Trigger x1
Control Terminals	Serial Connector: RS-232 9 Pin (Male) USB Type Mini-B (Download and page up/down) RJ45 (LAN Control)
Dimensions (W x H x D)	15.9" x 9.01" x 12.7"
Weight	12.1 lbs (5.5 kg)
Power Supply	100 to 240 VAC, 50/60 Hz
Power Consumption	315W (Typical), Standby <1W
Noise Level	33/27 dBA (Normal/Economical Model)
Display Languages	Bulgarian/Croatian/Czech/Danish/Dutch/English/Finnish/ French/German/Hungarian/Italian/Japanese/Korean/ Norwegian/Polish/Romanian/Russian/Simplified Chinese/ Spanish/Swedish/Turkish/Thai/Traditional Chinese
Picture Mode	Cinema/Dynamic/Presentation/sRGB/User 1/User 2
Functions	0.24 Throw Ratio/3D-Ready/LAN Control & Display/USB Display & Reader/Built-In 20W Speaker and Microphone-In/Digital Zoom x2/Closed Captioning/Quick Cooling/Panel Key Lock/Window 7/ Wireless Display (Optional)
Accessories (Standard)	User Manual (CD)/Power Cable/Quick Start Guide/Batteries/ Remote Control/D-Sub Cable/Warranty Card
Accessories (Optional)	Spare Lamp Kit/Wireless Dongle/0.3 Wall Mount
Lamp P/N	5J.J3A05.001
Limited Warranty	3-Years Parts & Labor / 1-Year or 2000 hours of lamp life

BenQ is a registered trademark of BenQ Corp. DLP® is a registered trademark of Texas Instruments. All rights reserved. Corporate and trademarks are the property of their respective companies. Specifications subject to change without notice.

MW881UST-EDU122110-US

BenQ America Corp.

15375 Barranca Parkway, Suite A-205, Irvine, CA 92618 • Tel: (949) 255-9500 • www.BenQ.us