1100 ANSI Lumens

XGA Resolution

HDTV Compatible

B O X L I G H T

# XP-8ta

The Boxlight XP-8ta is a price-sensitive, ultra-portable XGA LCD projector featuring advanced video capabilities. The XP-8ta is HDTV compatible and has component video input making this unit ideal for video applications. This remarkable unit weighs only 6.17 pounds, and has premium features like XGA resolution, 1100 lumens, manual zoom and focus, digital keystone adjustment and digital zoom. The Boxlight XP-8ta is a value-packed projector, perfect for both video applications and busy presenters on the go. Call the digital projector specialists at BOXLIGHT today.


*19332 Powder Hill Place*

*Poulsbo, WA 98370*

*800.762.5757*

*360.779.7901*

*www.boxlight.com*


BOXLIGHT®
Presenting a Better Way


BOXLIGHT and the BOXLIGHT logo are registered trademarks of BOXLIGHT Corporation. © 2004 BOXLIGHT Corporation.
All other marks are the property of their respective owners. Specifications are subject to change without notice. M1-XP8ta - 02/04

B O X L I G H T

# XP-8ta

p r o j e c t o r

- ***True 1024x768 XGA, with compression up to 1280x1024 SXGA***
- ***6.2lbs. / 2.8kg***
- ***1100 ANSI lumens***
- ***Digital Keystone adjustment on remote***
- ***Manual zoom/focus***
- ***Digital Zoom Imaging***
- ***Power Management function***
- ***Component Video Input***
- ***HDTV compatible***
- ***DRIT (Digital Realized InterpolationTechnology)***
- ***FCC Class B rating***

BOXLIGHT®
Presenting a Better Way

**To contact BOXLIGHT:**

| | |
|---|---|
| Direct | 800.762.5757 |
| Rental | 800.736.6954 |
| Education | 800.689.6676 |
| Government | 800.497.4009 |
| International | 360.779.7901 |
| Toll Free Fax | 888.353.4242 |
| Internet | www.boxlight.com |


| | | | |
|---|---|---|---|
| **Resolution:** | 1024 x 768 XGA with compression up to 1280 x 1024 SXGA | **Scan Frequency:** | 15–100kHz |
| **Brightness:** | 1100 ANSI lumens (MAX) | **Vertical Refresh Rate:** | 50–100Hz |
| **Lamp:** | 132W UHP | **Audible Noise:** | N/A |
| **Projection Lens:** | Manual zoom & focus 1:1.2 zoom ratio, F/1.6-1.78, f=1.13-1.36" | **Audio:** | Built-in 1 watt speaker |
| | | **Video:** | NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 575i, 575p, 720p, 1035i, 1080i |
| **Throw Distance:** | 5.3'–26.6' / 1.6-8.1m | | |
| **Display Type:** | (3) 0.7" TFT polysilicon LCDs | **Keystone:** | Digital adjustment of +/- of 20° horizontal |
| **Contrast Ratio:** | 300:1 | **Adjustments:** | On-board and remote |
| **Colors:** | 16.7 million | **Power Supply:** | 100–240V AC; 50/60Hz auto change |
| **Aspect Ratio:** | 4:3, 16:9 compatible | **Power Consumption:** | 250 watts |
| **Inputs:** | **Computer:** (1) RGB computer (15-pin), computer mini-jack audio; **Audio:** (1) A/V mini-jack; **Video:** (1) S-Video, (1) RCA composite/component video | **FCC Rating:** | n/a |
| | | **Dimensions (HxWxD):** | 3" x 10.1" x 9" / 7.58 x 25.7 x 22.9cm |
| | | **Weight:** | 6.2 lbs. / 2.8kg |
| **Outputs:** | **Computer:** (1) control port for mouse operation, (1) USB mouse control port; **Audio:** (1) external mini-jack audio | **Warranty:** | Two-year parts and labor (120 days or 500 hours, whichever comes first, lamp guarantee) |

**Specifications are subject to change without notice.**

**© 2004 BOXLIGHT Corporation.**