CD737x



BRIGHTNESS
3000 ANSI lumens

RESOLUTION
1024 x 768 true XGA
compressed 1280 x 1024 SXGA

DISPLAY TYPE
.7" DDR DLP XGA chip

CONTRAST RATIO
2000:1

WEIGHT
7.8lbs / 3.55kg

DIMENSIONS
12.9 x 3.5 x 9.4 in
32.8 x 8.8 x 23.8 cm

LAMP
250 watts VIP

LAMP LIFE
2000 hours

DIAGONAL IMAGE SIZE
37 - 240 in / .94 - 6.1 m

PROJECTION LENS
manual zoom
1.22:1 zoom ratio

THROW DISTANCE
4.9 - 26 ft / 1.5 - 8 m

AUDIO
1 x 2 watt speaker

Digital keystone adjustment, digital zoom imaging, a variety of video inputs and monitor loop-through are standard features of the CD737x. With 3000 lumens, 2000:1 contrast ratio and HDTV compatibility, your images will be crisp and bright.

rear view



Automatic set-up and direct key access for major functions make the CD737x easy to use

SPECIAL FEATURES:

Digital Keystone Adjustment
Create a uniform image on screen in virtually any environment.

HDTV Compatible
Compatible with 1080i, 720p HDTV standards

Manual Zoom / Focus
Easy to set-up and adjust the screen size for presenting in variable room conditions

Multiple Inputs
Connect to multiple computers and peripheral systems at the same time.

INPUTS
Computer: 1 - DVI-I
1 - RGB
Video: 1 - RCA composite
1 - S-Video
1 - Component
Audio: 1 - RCA (L/R)
1 - USB port
RS-232 Network

OUTPUTS
1 - RGB computer out
1 - 3.5 Stereo jack audio out

KEYSTONE
+ / - 15° vertical

VIDEO
NTSC, PAL, SECAM

FCC CERTIFICATION
Class B

DECIBEL RATING
33dB / 30dB eco

POWER SUPPLY
100 - 240 V
UL Certified

SHIPS WITH:

Remote Control	Lens cap
USB mouse cable	S-Video
Composite AV cable	Soft Carry Case
Power cord	User Manual
DVI-I (15 pin computer)	

WARRANTY:
Two year parts and labor (120-day/500 hour lamp guarantee)

BOXLIGHT®
Presenting a Better Way

19302 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct - 800.762.5757
International - 360.779.7901
Partners - 866.688.3636

2006 BOXLIGHT Corporation. All rights reserved. Specifications are subject to change without notice