

Pro3500p / Pro4500p

FEATURES:

Multiple inputs with RJ-45
Power lens shift
Progressive scan function
Digital horizontal & vertical
keystone adjustment
Picture in picture

SHIPS WITH:

Remote control
User manual
Power cord
RGB cable
M1-D cable
Audio/Video cable
Lens cap


WARRANTY:

Three year parts and labor
90-day lamp guarantee

OPTIONAL ACCESSORIES:

Mac adapter
Ceiling mount
ATA case
Kensington lock
Wide fixed lens
Short throw lens
Ultra long throw lens
Replacement lamp

www.boxlight.com/procolor
866.688.3636
19302 Powder Hill Place
Poulsbo, WA. 98370



BRIGHTNESS

Pro3500 - 3500 ANSI lumens
Pro4500 - 4500 ANSI lumens

RESOLUTION

True 1024 x 768 XGA
Compressed 1600 x 1200 UXGA

DISPLAY TYPE

3 - 0.99 in TFT polysilicon LCDs
with Micro Lens Array (MLA)

CONTRAST RATIO

800:1

LAMP

pro 3500 - 275 watt UHB
pro 4500 - 310 watt UHB

LAMP LIFE

2000 hours

COMPATIBILITY

UXGA, SXGA, XGA, SVGA, VGA, Mac

PROJECTION LENS

Power zoom 1:1.5 zoom ratio
F/1.7 - 2.4, f=31 - 46 mm

INPUTS

(1) 15 Pin computer
(1) M1-D, (1) BNC, (1) composite
(1) S-Video, (1) component
(2) Audio mini jacks

OUTPUTS

(1) 15 Pin computer out
(1) USB mouse

THROW DISTANCE

1.5 - 2.2 : 1 mm
(distance : width)

KEystone

Vertical adjustment of + / - 15°
Horizontal adjustment of + / - 5°



*Conference room presentations
are instantly brighter with the
ProColor 3500p/4500p multimedia
projector. Featuring 3500 / 4500 ANSI
lumens and 800:1 contrast ratio, this
XGA unit is ideal for bright, detailed
images in large venues. This well
designed unit includes power lens shift,
optional zoom lenses and an easy-to-
replace lamp to simplify installations.*

VIDEO

NTSC, NTSC4.43, PAL, PAL60, SECAM, PAL-M,
PAL-N, 480i, 575i, 480p, 1080i, 720p

AUDIO

Dual 1-watt speakers

POWER SUPPLY / CONSUMPTION

AC100 - 120V, 220-240 V

DECIBEL RATING

35dB in whisper mode

DIMENSIONS

16.5 x 6.3 x 12.6" in
41.91 x 16.00 x 32.00 cm

WEIGHT

17 lbs / 7.71kg