Butterfly PFAX006







Brief Introduction

Beta 2.5

The PFAX006 LED LCOS projector from Butterfly has 100 Ansi lumens, a contrast of 200:1 and an XGA 1024 x 768 resolution. The manufacturer specifies an LED service life of 20000 hours, which is over 13.7 years if enjoyed for four hours a day. The projector will be able to illuminate a picture width of 87 cm well. However, if room light is available, the picture width should ideally not exceed 58 cm. This model is no longer offered by Butterfly.

Display Type

LCoS Panel

0,5000 min. Lumen

XGA 4/3 Liquid Crystal on Silicon (LCOS)

Ansi-Lumen Contrast

Projecto 100 ω33 Lux (bei 200 cm Screen) 200:1 full on/off

Black Level Offset

ชู้ 200:1 full on/off [™] 0,168 min. Lumen

Resolution

XGA 1024 x 768 786.432 Pixel

Video Modes Application

Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p Game-Portabel | Very portable, small-screen projections. Very narrow picture width and rooms with very little light.

Light Source Light Life

3LED 20000 h.

Operating Costs

0,00 € LED

Focus Zoom

Manual

No Zoom

Objective

Throw Ratio

2,1:1

Audio

HDMI in

Connections

D-sub 15pin in Cinch Video in SD-Slot in

Ceiling Mounting Power

Yes 50W

Size WxHxD

130 x 49 x 138 mm (5,1"x1,9"x5,4") 0,88 L/dm3

Operating Noise

Weight Keystone 0,475 kg / 1,05 lbs.

Illumination

Frequenz

Foot-Lamberts

3 fL / max. 87 cm screen width

10 cd/m²

Features

Status Data

2013 Discontinued (EOL) // Last update of the data: 2023-08-04



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.