

# CASIO®

## XGA

## Model XJ-A130 2000 Lumens



## Never Change a Mercury Lamp Again! You Could Save Up to \$800.\*

You could save up to \$800 based on a comparison to prior Casio product with a mercury Lamp.  
At only 1.7 inches thick it is the thinnest high brightness projector in the industry. +

### 2X ZOOM

#### 2X OPTICAL ZOOM

The 2X Optical Power Zoom makes it easier to fit your presentation on the screen.

### HDMI

#### HDMI

Direct Digital Input

#### VALUE AND A GREAT WARRANTY

Estimated Light Source  
Life is 20,000 hours.  
3 years Casio warranty.\*



#### CONSISTENT BRIGHTNESS & COLOR

The new hybrid light source loses less than 3% in 2,000 hours. Casio mercury lamps lose 50% of brightness in 2,000 hours.

### CONSISTENT BRIGHTNESS & COLOR

#### SUPER COLOR

Hybrid light source results in more than double the color spectrum compared to previous Casio mercury lamp projectors. This results in richer color.

### SUPER COLOR

PICTURE BY DLP



## GREEN SLIM PROJECTOR



Mercury Free

visit: [www.greenslimprojector.com](http://www.greenslimprojector.com)

\*Based on comparison to prior Casio product with mercury lamp. Scheduled lamp change is every 2,000 hours at a cost of \$400 per lamp. This product warranty is for 3 years or 6,000 hours as measured by internal projector timer. See warranty at [www.greenslimprojector.com](http://www.greenslimprojector.com) for full details. + Based on Casio research of high brightness (over 2000 lumens) projectors January, 2010.

| BASIC SPECIFICATIONS                             |                       |                                                                                                                                        |
|--------------------------------------------------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Brightness                                       |                       | 2000 lumens                                                                                                                            |
| Contrast ratio                                   |                       | 1800 : 1                                                                                                                               |
| Projection lens                                  |                       | 2X Power zoom & focus                                                                                                                  |
| Lens offset                                      |                       | 100%                                                                                                                                   |
| Light Source                                     |                       | Laser & LED hybrid technology                                                                                                          |
| Estimated Operating Life                         |                       | up to 20,000 hours (waranty 3 years or 6,000 hours)                                                                                    |
| Projection screen size                           |                       | 15 ~ 300-inch                                                                                                                          |
| Projection range                                 | 60-inch screen        | 5.6 ft ~ 11.2 ft                                                                                                                       |
|                                                  | 100-inch screen       | 9.24 ft ~ 18.48 ft                                                                                                                     |
|                                                  | Minimum               | 2.77 ft                                                                                                                                |
|                                                  | Projection ratio      | 1.4-2.8:1                                                                                                                              |
| Projection system                                |                       | DLP® system                                                                                                                            |
| Display element                                  | Device Type           | 0.55-inch DLP® chip                                                                                                                    |
|                                                  | Native Resolution     | XGA (1024 x 768) 786,432 pixels                                                                                                        |
|                                                  | Native Aspect Ratio   | 4.3                                                                                                                                    |
| Color reproduction                               |                       | Full color (16.77 million colors)                                                                                                      |
| Power source                                     |                       | AC100~240V, 50/60Hz                                                                                                                    |
| Keystone correction                              | Auto                  | +30° Vertical                                                                                                                          |
|                                                  | Manual                | ±30° Vertical                                                                                                                          |
| Dimensions                                       |                       | 11.69" x 8.26" x 1.69" incl. projections<br>(1.58" at thinnest point excl. projections)                                                |
| Weight                                           |                       | 5.0 lbs                                                                                                                                |
| Ceiling mount                                    |                       | Yes (mount available separately from 3rd party vendors)                                                                                |
| Power consumption                                | Operating             | 270W (Eco Off) / 190W (Eco On Level 1) / 130W (Eco On Level 2)                                                                         |
|                                                  | Standby               | 100 - 120V (0.4W), 220 - 240V (0.6W)                                                                                                   |
| Security compatibility                           | Kensington compatible | Yes                                                                                                                                    |
|                                                  | Power ON password     | Yes                                                                                                                                    |
| INTERFACE TERMINALS                              |                       |                                                                                                                                        |
| RGB/Component Video Input                        |                       | mini D-Sub 15 pin x 1<br>Also use as YcbCr/YPbPr input                                                                                 |
| Native Resolution                                |                       | XGA (1024 x 768) 786,432 pixels                                                                                                        |
| Computer Signal Compatibility (max.) Resolutions |                       | UXGA (1600 x 1200) (Compressed)<br>SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA                                                    |
| Digital input                                    |                       | HDMI x 1 (480P ~ 1080P)                                                                                                                |
| Audio                                            | Input                 | 3.5mm mini-jack                                                                                                                        |
|                                                  | Output                | 1 W speaker<br>3.5mm mini-jack (shared with Audio Input)                                                                               |
| Video                                            | Input terminals       | Composite: 3.5mm mini-jack<br>(sharing audio terminal ), YCbCr/YPbPr Keystone correction                                               |
| Video Signal                                     | Video Systems         | NTSC/PAL/PAL-N/PAL-M/<br>PAL60/SECAM                                                                                                   |
| Compatibility                                    | DTV/HDTV              | 480i/480P/576i/576P/720P/1080i/1080p                                                                                                   |
| Control                                          | Terminal              | RS-232C. adapter cable (YK-5)<br>required and sold separately                                                                          |
| OTHERS                                           |                       |                                                                                                                                        |
| Usage environment                                | Operating temperature | 41~95°F                                                                                                                                |
|                                                  | Operating humidity    | 20~80% (non-condensation)                                                                                                              |
|                                                  | High Altitude Mode    | Yes (for operation 3,300~6,600 ft)                                                                                                     |
| Remote controller range                          |                       | 16.5 ft maximum                                                                                                                        |
| Limited Warranty                                 |                       | 3 years Parts and Labor plus 3 years or 6,000 hour light source<br>(see Warranty Statement included with product for complete details) |
| Included Accessories                             |                       | Wireless remote control, RGB cable, AV cable, AC Power Cord,<br>Projector & Accessory Soft Case, Manual on CD-ROM and booklet          |
| Optional Accessories                             |                       | YK-5 (RS-232C adapter)<br>YK-CASE01 (Soft Carry Case with handle and shoulder strap)                                                   |
| UPC Code                                         |                       | 0-79767-18431-5                                                                                                                        |
| Carton Dimensions                                |                       | 14.96 W x 6.22" H x 10.43" D                                                                                                           |
| Carton Weight                                    |                       | 10.14 lbs                                                                                                                              |

visit: [www.greenslimprojector.com](http://www.greenslimprojector.com)



CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA and WXGA are registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners. Specifications subject to change without notice.