

you're convinced that  
you can't be impressed by anything...  
anymore....



...give us a try!

***DreamVision***  
*There must be one for you*



|                                          |                                                                            |
|------------------------------------------|----------------------------------------------------------------------------|
| PROJECTION:                              |                                                                            |
| Projection system                        | 3 x DMD TM HD2 chip                                                        |
| <input type="checkbox"/> 1280x720 pixels |                                                                            |
| Lenses                                   | Standard Zoom lens G100 Minolta                                            |
| Throw Ratio                              | 1.44 – 1.8:1                                                               |
| Zoom Ratio                               | 1:1.25                                                                     |
| Zoom                                     | Motorized zoom                                                             |
| Focus                                    | Motorized focus                                                            |
| Shift                                    | Electrical H and V shift                                                   |
| <input type="checkbox"/>                 | +100%, -50% Vertical                                                       |
| <input type="checkbox"/>                 | +/- 20% Horizontal                                                         |
| Keystone                                 | adjustable 22 degrees max.                                                 |
| Lamp                                     | 250W                                                                       |
| <input type="checkbox"/>                 | 1500 hrs. average life time                                                |
| Brightness                               | 1800 ANSI lumens                                                           |
| Installation                             | Front/rear floor /ceiling mounted.                                         |
| Horiz. scan freq.                        | 15-80KHz (max horizontal frequency corresponding to 1600x1200, 60Hz).      |
| Vert. Scan freq.                         | 48 - 100Hz                                                                 |
| Contrast ratio                           | 2800:1.                                                                    |
| Colour temperature                       | Various                                                                    |
| Colour system                            | All                                                                        |
| Video Format board                       | Powered by the Faroudja FLI2310, the video processor Pixelworks PW 365 and |
| <input type="checkbox"/>                 | Sil9993 HDCP compliant HDMI decoder IC. DVI-HDMI-RS232 Board including DVI |
| <input type="checkbox"/>                 | (NO. N HDCP Sil161) connector, HDMI connector and Serial Port Connector.   |
| Keypad                                   | 8 keys                                                                     |
| Memories                                 | 3 memories x 24 inputs user definable memories                             |
| Test pattern                             | Six internal test patterns                                                 |
| VIDEO STANDARDS                          |                                                                            |
| Graphics:                                | VGA, XGA, SXGA, UXGA, WXGA                                                 |
| Composite Video                          |                                                                            |
| Color standards:                         | PAL B,G,H,I,M,N,60,SECAM, NTSC 3.58,, NTSC 4.43,                           |
| <input type="checkbox"/>                 | A TSC HDTV: 480p, 1080i, 720p and all the others                           |
| INPUTS/OUTPUTS:                          |                                                                            |
| <input type="checkbox"/>                 | 1x RGB/y-YcCrCb (RCA connectors)                                           |
| <input type="checkbox"/>                 | 1x RGB Y/V – YcCrCb (BNC connectors)                                       |
| <input type="checkbox"/>                 | 1x S-VHS (mini DIN 4 pins connector)                                       |
| <input type="checkbox"/>                 | 1x Video CVBS (RCA connector)                                              |
| <input type="checkbox"/>                 | 1x DVI (DVI – D connector)                                                 |
| <input type="checkbox"/>                 | 1x HDMI on HDMI connector fully HDCP compliant                             |
| <input type="checkbox"/>                 | 1x VGA (15pins connector)                                                  |
| <input type="checkbox"/>                 | 1x RS232 serial port connector (DB9 connector);                            |
| <input type="checkbox"/>                 | 2x 12v remote screen control (jack connectors)                             |
| <input type="checkbox"/>                 | 1x HDMI Audio Output via SPDIF connector                                   |
| POWER SUPPLY:                            |                                                                            |
| Mains voltage                            | range: 100 - 240 Vac, ± 10%                                                |
| Mains frequency                          | range: 48/62 Hz                                                            |
| OTHERS                                   |                                                                            |
| Supplied accessories                     | AC power cables (EU, UK and USA); Length : 2m                              |
| Weight                                   | 25kg                                                                       |
| Dimensions                               | 517 (L) x 622 (W) x 260 (H) mm                                             |
| OPTION                                   |                                                                            |
| <input type="checkbox"/>                 | Ceiling Bracket                                                            |
| <input type="checkbox"/>                 | Optional Lenses                                                            |

The specifications can be modified without prior notice

3 x HD2 chip DLP

Native 16:9 Aspect Ratio

Stylish Design

Easy Integration

Motorized Zoom

Motorized Focus

H and V Lens Shift

User Definable Memories

8 Video Inputs

5 Optional Lenses

Distributed by:

List of available Optional Lenses

| Model       | GR-1 | GR-80    | G-200   | G-400   | G-500   |
|-------------|------|----------|---------|---------|---------|
| Throw Ratio | 0.64 | 1.2-1.44 | 1.8-2.4 | 2.4-3.6 | 3.6-5.6 |