

ImagePro 8410 DLP Projector

Bright, Feature Rich and Portable

Robustly featured and powerfully portable, the 3D Ready ImagePro 8410 is designed for maximum versatility and low-cost operation. With 4000 ANSI lumens and an 8-watt speaker, the 8410 delivers exceptional brightness and rich audio wherever the presentation – in large conference rooms, meeting rooms, training facilities or classrooms. With extensive connectivity options, including RJ45 for remote management and control, the 8410 is ready for the most demanding applications.

*3D source, 3D content and 3D glasses are required for 3D viewing

Features

- Easy-to-read text – bright at 4000 ANSI lumens; high contrast ratio of 3000:1
- Enter the 3rd dimension to deliver outstanding education, training and gaming images
- Standby VGA and audio pass-thru feature reduces power consumption
- Built-in 8-watt speaker
- Remote control and management via RS-232 or RJ45
- Broad range of audio and video connectivity



Specifications

Display Technology

Single 0.55" DMD DLP Technology by Texas Instruments

Resolution

Native XGA (1024 x 768)

Maximum Resolution

UXGA (1600 x 1200)

Brightness (Typical)

4000 ANSI Lumens

Contrast Ratio

3000:1 (Full On/Full Off)

Lamp Life and Type

3000/2000 Hours (STD/Bright)
280W P-VIP

Throw Ratio

1.6 to 1.92:1 (Distance/Width)

Projection Distance

3.93' to 32.8' (1.2 to 10m)

Image Size (Diagonal)

30" to 307" (0.92 to 9.21m)

Offset

115%

Displayable Colors

1.07 Billion

Uniformity

85%

Audio

8-Watt Speaker

Remote Control

Fully Featured IR Remote with Mouse and Laser Pointer

Computer Compatibility

UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

Loop Through

Monitor: D-Sub 15-Pin VGA Output
Audio: Stereo Mini-Jack Output
(Functional in Both Normal and Standby Modes)

Projection Lens

F=2.4-2.66, f=18.2-21.8mm, 1.2x Manual Zoom and Focus

User Controls

Complete On-Screen Menu Adjustments in 23 Languages

I/O Connectors

HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, RJ45, RS-232, USB and 12V trigger.

Security

Kensington® Lock, Security Bar and Keypad Lock

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

6.4 lbs (2.9kg)

Dimensions (W x H x D)

12.76" x 3.82" x 9.21"
(324 x 97 x 234 mm)

Noise Level (STD/BRIGHT)

29dB/31dB

Keystone Correction

±40° Vertical

Horizontal Scan Rate

15.3 - 91.1 KHz

Vertical Refresh Rate

24 - 120 Hz

Operating Temperature

41 to 104°F (5 to 40°C), 85% Max Humidity

Power Supply

AC Input 100-240V, 50-60Hz, Auto-Switching

Power Consumption

372 Watts Max (Bright), 314 Watts (STD), <1 Watt (Standby)

Standard Accessories

AC Power Cord, VGA to VGA Cable, USB Cable, Remote Control, Batteries for Remote, USB Cable, Carrying Case, Lens Cap, Multilingual CD-ROM User's Manual, Quick Start Card and Warranty Card

Specifications subject to change without notice.

5YR

Five (5) year limited warranty on parts and labor in North America.

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.



Convey by Dukane delivers control of classroom audio visual assets in sync with our Student Response System. Experience tomorrow's classroom today with Convey. Visit www.conveyclassrooms.com.

Audio Visual Products
2900 Dukane Drive • St. Charles, Illinois 60174

Toll-free: 866-280-4298 • Web: www.dukane.com/av
Fax: 630-584-5156 • E-mail: avsales@dukane.com

#10-00017.01