ImagePro 8805
Portable LCD Projector

- 3200 lumen brightness
- XGA resolution
- 800 to 1 contrast ratio
- Full connectivity
- Two PC card slots
- 4000 hour lamp life
- Quick install optional lenses
- Power zoom & auto focus
- Digital keystone correction
- Optional Wireless and wired LAN
- Automatic color correction
- Enhanced security features



8805 DUKANE

ImagePro 8805
Portable LCD projector

The Dukane ImagePro 8805™ is a versatile solution for the most demanding presentation requirements. Providing realistic colors, sharp contrast, and super bright images, the 8805 is sure to impress.

Auto focus, power zoom, and automatic color corrections make set up and operation fast and easy. Flexible connectivity, networking capability, and enhanced security features make the 8805 a great choice for classrooms, conference rooms, or other locations where a bright image is required.

From the lens to the connector panel, our environmentally friendly projector is precision crafted for performance, quality and long-term reliability.



Key features:

- 3200 lumen brightness
- XGA resolution
- 800 to 1 contrast ratio
- Full connectivity
- PC card slots
- 4000 hour lamp life
- Quick install optional lenses
- Lamp access on top of projector for easy changing in ceiling mounted applications
- Power zoom & auto focus
- Digital keystone correction
- Optional Wireless and wired LAN
- Automatic color correction
- Enhanced security features
- Two year warranty and One year Peace -of- Mind service

Specifications 8805

Image Element	1.0" polysilicon TFT x 3, MLA
Brightness	3200 ANSI lumens (2600 lumens in Whisper Mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	800:1
Scanning Frequency	fh 15-100 kHz, fv 48-120 Hz
Lens	Power zoom and focus F=1.74-2.18, Auto focus
Lens Throw Ratio	1.5-2.1:1 throw distance to image width
Keystone Correction	Digital, vertical +/-40 deg., horizontal +/-27 deg.
Aspect Ratio	4:3, 16:9, selectable
Computer Compatibility	SVGA, VGA, XGA, and SXGA/UXGA Compressed Mac 13" and Mac 16"
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, HDTV 1080i,1080i/50 Hz, 720p, 576p, 480i/p
Component Video, Image Control	Comp, horz res, 800TV line Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	275W NSH
Lamp Life	2000 hours, 3000 in whisper mode
Audio	2 x 5W with volume, bass, treble control
Throw Distance	29" to 826"
Screen Size, diagonal	25" to 500" diagonal
Inputs, Video	(1) Component, BNC x 3 (1) S-video, Min DIN 4-pin, with RCA audio (1) Composite video, with L/R RCA audio (1) Audio, Stereo, RCA x 2
Inputs, Computer	(1) DVI, with audio stereo mini jack (1) RGB Signal: D-sub, 15 pin and audio stereo mini jack (1) RGB Signal: 5-BNC (2) PC Card slot
Outputs Monitor	15 pin, D-sub with audio stereo mini jack
Outputs,Control	PC control DIN 8 pin, RS-232 Audio out, stereo, RCA x 2 Remote, mini jack, USB Type A & B
Security	Kensington slot and password
Fan Level	39dB, 34dB in whisper mode
Operating Temperature	32 to 95 deg. F (0-35 deg C)
Power	AC 100-120V, AC200-240V 50/60 Hz, 390 watt
Size (WxHxD)	13.2" x 4.6" x 12.8"
Weight	13 lbs.
Shipping Weight	22 lbs.
Carton Size	20" x 14" x 20"
Accessories Included	Remote control w/ laser pointer, power cord, computer cable, USB cable, remote control cable, CDROM, operators manual, USB mouse
Safety	UL/CUL, FCC Class B
Optional Accessories	Lamp 456-8805, Ceiling mount, universal; PJF-UNV-S

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year *Peace-of-Mind Loaner Program.*

2YR

DUKANE

Dukane Corporation
Audio Visual Products Division
2900 Dukane Drive
St. Charles, Illinois 60174
800-676-2485 or 2486 toll-free
630-584-5156 fax
avsales@dukcorp.com e-mail
www.dukcorp/av.com

ImagePro is a registered trademark of Dukane Corporation
#11631-D-04