

3 x 0,62" LCos Panel

SVGA 4/3 Liquid Crystal on Silicon (LCOS)

1500

ω 500 Lux (bei 200 cm Screen)

Lux:500 Lux

4/3 screen width:200 cm

Screen:1 Gain

Room light max.:100 Lux Candela pro m<sup>2</sup>:158 cd/m<sup>2</sup>

Foot-Lamberts:46 fL

Offset

SVGA 800 x 600 480.000 Pixel

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product presentations.

Small screen width, rooms with very little ambient light below 100 lumens. 50W HID Lamp

Operating Costs -

Zoom

Throw Ratio

Audio 2 x Stereo Speakers

D-sub 15pin in

YUV in Connections

Cinch Video in

Cinch Stereo in

Ceiling Mounting Power

Size WxHxD

238,8 x 119,4 x 215,9 mm (9,4"x4,7"x8,5") 6,09 L/dm<sup>3</sup>

Operating Noise

Weight Keystone Illumination

Frequenz

Foot-Lamberts 46 fL / max. 337 cm screen width

158 cd/m<sup>2</sup>

**Features** 

Data

2007 Discontinued (EOL) // Last update of the data: 2023-08-04

https://www.projector-database.com/pro/dynadypj002-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.

Display Type

Ansi-Lumen Contrast

Black Level

Resolution

Video Modes

Application

Light Source

Light Life

**Focus** 

Objective

Status

More Details