



C835

8,300 center lumens bright with 80% uniformity and a 5,000,000:1 contrast ratio.
Native WUXGA resolution. Compatible with inputs up-to UXGA, WUXGA and 4K.
Supports analog and digital video input in all color standards up-to 1080p.
Supports 4K (3840x2160@60Hz) video input via HDMI.
Convenient mid-range (1.6:1) manual zoom and focus lens.
Horizontal, Vertical & Corner Keystone Correction.
Pincushion/Barrel & 6 point Geometric Correction.
Horizontal & Vertical Manual Lens Shift. Wired network control.
Displays 4:3, 16:9 and 16:10 aspect ratios. Supports most HDTV resolutions.
Built-in 16 Watt sound system. Closed Caption decoding (NTSC).
Side-accessed air filter for ease of maintenance.
Auto input selection. Built-in Test Patterns.
Security bar. Kensington® MicroSaver® security slot. PIN lock.
3 year Projector warranty. 20,000 hour Laser Light Engine warranty.

Included Accessories:


Quick Start Guide, HDMI Cable, Detachable Power Cord, Remote Control

Optional Accessories:

Replacement Filter, Ceiling Mount, Ceiling Post and Plate

C835

8,300 Lumens / WUXGA / 3LCD
Laser + Phosphor Light Engine
Accepts inputs up-to 4K
Crestron RoomView™ & AMX Device Discovery Technology



Specifications: Model C835

Brightness	8,300 Center Lumens	Image Signal Resizing	Smart Scaling Technology
Contrast Ratio	5,000,000:1	Image Signal Inputs	
Illumination Uniformity	80%	Computer 1	Dsub15 x 1
Resolution and Aspect Ratio	WUXGA (1920x1200), 16:10	Digital Video (w/ HDCP)	HDMI x 2
Color Reproduction	10-bit (16.7 million colors)	HDBaseT	RJ45 x 1
Projection Light Source	Laser (Blue) + Phosphor	USB-A - Memory Viewer	USB Type A x 1
Estimated Light Source Life	20,000 hours	USB-B - USB Display / Firmware	USB Type B x 1
Total Pixels	6,912,000 (1920x1200) x 3	Audio Signal Inputs	
Imaging System	0.64 in (16 mm) inorganic LCD Panels x 3	Computer Audio	MiniStereo x 1
Scanning Frequency	Auto: H Sync. 15-100 KHz, V Sync. 24-85 Hz	Outputs	
Pixel Clock	up-to 160 MHz	Computer Monitor	Dsub15 x 1
Lens	Attached - Manual Zoom and Focus	Audio Output	Variable, Stereo: MiniStereo x 1
Lens Specs	f: 1.5-2.08; FL: 0.677-1.09 in (17.2-27.7 mm)	Speaker	Mono: 16 Watt
Lens Ratios	Zoom Max:Min: 1.6:1; Throw:Width 1.2-2.0:1	Fan Noise (Eco / Normal)	29 dB / 39 dB
Image Diagonal	30-300 in (76.2-762 cm)	Cabinet Size (HxWxD) - excluding legs	5.4 x 15.9 x 14.1 in (13.7 x 40.5 x 35.8 cm)
Image Width	2.1-21.2 ft (0.64-6.4 m)	Weight	17.4 lb (7.9 kg)
Throw Distance	2.5-42.0 ft (0.77-12.8 m)	Packaged Cabinet Size (HxWxD)	10.0 x 19.9 x 19.1 in (25.5 x 50.5 x 48.4 cm)
Lens Shift	V: + 60% H: +/- 29%	Packaged Weight	22.9 lb (10.4 kg)
Projector Elevation Adjustment (legs)	Up-to 3.5°	Operating Temperature	41-104°F (5-40°C)
Maximum Pitch	Up-to 360° Installation	Electrical Safety Compliance	IEC / UL / cUL
Vert/Horiz. Keystone Correction	Digital: V: +/- 30° H: +/- 30°, Corner Keystone	Electromagnetic Compatibility	FCC Class B, CE Mark
Image Orientation	Normal, Reversed, Inverted	Power Requirements	100-240V AC, 50/60 Hz
Local Control / Power Management	Full Function / Auto Shutdown	Power Consumption	0.5 W in Eco Standby mode, up-to 425 W
Remote Control	Wireless x 1	Heat	1,450 BTU
RS-232 Control	Dsub9 x 1	Security Facilities	Kensington® Security Slot
LAN Port	RJ45 x 1	User Maintenance	Clean Filter
Computer Input in Pixels	up-to 1600x1200 (4:3), 3840x2160 (16:9)	Limited Warranty: to the original end use customer only	
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA	Projector	*3 years / 6,000 hours
Analog Wide Inputs	WUXGA, WSXGA+, WXGA	Laser Light Engine only	*3 years / 20,000 hours use (whichever occurs first)
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA		
Digital Wide Inputs	4K, WUXGA, WSXGA+, WXGA		
Video Formats	NTSC / PAL / SECAM		
Video Input Analog	480i/p, 576i/p		
Video Input Digital	480p, 576p, 720p, 1080i/p		

EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. © Eiki International Inc. Issued September 17, 2025
Eiki International Inc., 22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 Email: usa@eiki.com