

RS232C Communication Format for EIP-S200 & EIP-X200

1. Communication Protocol

Standard Baud rate: 9600 bps
Data length: 8 bits
Parity: None
Stop bit: 1 bit
Flow Control: None

2.After receiving command, response same string.

3.Command List

Command	Function	Remarks
POWR__1	Power On	"__" means 3 spaces.
POWR__0	Power Off	
IRGB__1	Input1(analog RGB)	
IVED__1	Input2(Video)	
ISEV__1	Input3(S-VIDEO)	
ICMP__1	Input4(Component)	
IMBK__1	V-Mute On	
IMBK__0	V-Mute Off	
ADJS__1	Auto Sync	
IMEN__1	Osd Menu key	
IMUP__1	Osd Up key	
IMDN__1	Osd Down key	
IMLE__1	Osd Left key	
IMRI__1	Osd Right key	
IBLK__1	Blank	
IKSU__1	Keystone Up	
IKSD__1	Keystone Down	
IASP__1	Aspect Ratio (4:3 16:9)	
IVUP__1	Volume+	
IVDN__1	Volume-	
IECO__1	Eco On	
IECO__0	Eco Off	
IBRI__1	Brightness+	
IBRI__0	Brightness-	
ICNT__1	Contrast+	
ICNT__0	Contrast-	

•