




EIP-WSS3100

3,100 ANSI Lumens / WXGA / DLP®
Ultra Short Throw Series Projector
Optional Interactive Features

EIP-WSS3100

3,100 ANSI lumens bright with 80% uniformity and a 8000:1 contrast ratio.
HDMI Digital connectivity with HDCP compliance. 1-chip DLP® technology.
Native WXGA resolution. Compatible with inputs up-to UXGA and WSXGA+.
Supports analog and digital video input in all color standards up-to 1080p.
Compatible with Crestron RoomView™ & AMX Device Discovery Technology.
Interactive Features Optional. 3D Ready.
Ultra-Short Throw projector (0.35:1) manual focus lens.
Accepts composite, component, and S-Video in all major standards.
Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.
Built-in 10 Watt sound system. Closed Caption decoding (NTSC).
Wired network monitoring and control. Digital zoom: 2X
Side-accessed lamp and air filter for ease of maintenance.
Color board modes. Custom warm-up screen. Auto input selection.
Security bar. Kensington® MicroSaver® security slot. PIN lock.
3 year projector warranty.



Included Accessories:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with Lithium Battery CR2025)

Optional Accessories:

Replacement Lamp, Component Video Input Cable (Dsub15 to 3RCA), Ceiling Mount, Ceiling Post and Plate, IR Pen and 2 AAA Batteries, IR Pointer and 2 AAA Batteries, IR Camera, Interactive Software on CD, USB Cable

Specifications: Model EIP-WSS3100

Brightness	up-to 3,100 ANSI Lumens	Image Signal Inputs	
Contrast Ratio	up-to 8000:1	Computer 1 / Component (w/optional adapter)	Dsub15 x 1
Illumination Uniformity	80%	Computer 2 / Component (w/optional adapter)	Dsub15 x 1
Resolution and Aspect Ratio	WXGA (1280x800), 16:10	HDMI / Digital PC / Digital Video (w / HDCP)	HDMI x 1
Color Reproduction	10-bit (1.07 billion colors)	S-Video	S-Video x 1
Projection Lamp	280 Watts UHP	Composite Video	RCA x 1
Estimated Lamp Life	up-to 4,000 hours	Interactive Features / Firmware Upgrade	Mini-USB Type B x 1
Total Pixels	1,024,000 (1280x800) x 1	Audio Signal Inputs	
Imaging System	0.65" DMD™ DLP® chip x 1	Computer Audio	MiniStereo x 2
Color Wheel	6 segments x 1	Video Audio	RCA (L/R) x 2
Scanning Frequency	Auto: H Sync. 30-100 kHz, V Sync. 50-120 Hz	Microphone	MiniStereo x 1
Pixel Clock	up-to 170 MHz	Outputs	
Lens	Attached - Manual Focus	Computer	Dsub15 x 1
Lens Specs	Speed: f: 2.6; FL: 0.193 in (4.90 mm)	Audio Output	Variable, Stereo: MiniStereo x 1
Lens Ratios	Throw:Width 0.35:1	Screen Trigger	DC12V x 1
Image Diagonal	70-100 in (178-254 cm)	Amplifier	Mono: 10 Watt
Image Width	4.9-7.0 ft (1.5-2.1 m)	Speaker	1.4 in (3.7 cm) x 1 (Mono)
Throw Distance	23.5-28.8 in (597-731 mm)	Fan Noise	as low as 33 dBA
Projector Elevation Adjustment (legs)	up-to 5.9°	Cabinet Size (HxWxD)	9.1 x 14.1 x 14.5 in (23.1 x 35.7 x 36.7 cm) (including mirror - excluding legs)
Vertical Keystone Correction	Digital: up-to 15° Up or Down	Weight	17.5 lb (8.0 kg)
Image Orientation	Normal, Reversed, Inverted	Packaged Cabinet Size (HxWxD)	13.9 x 18.3 x 17.9 in (35.3 x 46.4 x 45.4 cm)
Local Control / Power Management	Full Function / Auto Shutdown	Packaged Weight	22.0 lb (10 kg)
Remote Control	Wireless x 1	Operating Temperature	41-95°F (5-35°C)
RS-232 Control	Dsub9 x 1	Electrical Safety Compliance	IEC / UL / cUL
LAN Port	RJ45 x 1	Electromagnetic Compatibility	FCC Class B, CE Mark
Computer Input in Pixels	up-to 1600x1200 (4:3), 1680x1050 (16:10)	Power Requirements	100-240V AC, 50/60 Hz
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Power Consumption	0.5 W in Eco Standby mode, up-to 350 W
Analog Wide Inputs	WSXGA+, WXGA+, WXGA	Heat	up-to 1,195 BTU/hr
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Security Facilities	Security Bar, Kensington® Security Slot
Digital Wide Inputs	WSXGA+, WXGA+, WXGA	UPC	4571194676389
Video Formats	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N	User Maintenance	Clean Filter, Replace Lamp
Video Input Analog	480i/p, 575i/p	Limited Warranty: to the original end use customer only	3 years
Video Input Digital	480p, 575p, 720p, 1080i/p	Projector	1 year ownership / 500 hours use (whichever occurs first)
Image Signal Resizing	Smart Scaling Technology	Lamp	

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.
EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.
DLP® and DMD™ are trademarks of registered trademarks of Texas Instruments.

Specifications subject to change without notice. ©2013 Eiki International Inc. Issued April 22 2013
Eiki International Inc., 30251 Esparanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, Email: usa@eiki.com
In Canada: 310 First St., Unit 2, P.O. Box 156, Midland ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, Email: canada@eiki.com