

Epson EB-E500 XGA 3LCD Projector

Product Models displayed on this website may be available in certain regions only.



Enhance the Classroom Experience with Expressive Projections.

Engage the young minds with expressive and vivid projections in class with this 3300 lumens XGA projector.



Overview

Outstanding flexibility and portability


The outstanding flexibility and portability makes it easy for you to install it anywhere in the classroom without additional hassle. Now you can capture and retain students attention to achieve maximum concentration.



Compelling Projection


Bring images to life in the classroom with Epson's XGA resolution projectors. Projecting up to 3,600 lm brightness*, you can now present your materials to the class with brighter pictures in better colours and contrasts. Leave a more convincing and stronger presentation to your peers and students with Epson's projectors today.

XGA Resolution
1024 x 768



Sharper, detailed images

SVGA Resolution
800 x 600



Loss of details

Various Interfaces

Epson business projectors support a wide range of connectivity options including HDMI, VGA, and USB. These interfaces support connections to both the latest digital devices as well as the existing legacy of analogue products without the need for adaptors.

Smart device



Computer




Game



USB




DVD/Blu-Ray Disc



Video Camera



Camera



Tuner/Player

Easy Maintenance and Longer Lamp Life

A long lamp life reduces maintenance and costs. The lamp will last up to 12,000 hours in ECO mode. Cut down on the frequency of lamp replacements, saving you time and money, and lowering the total cost of ownership.



Specifications

Projection Technology:

Projection Technology:

RGB liquid crystal shutter projection system (3LCD)

Brightness²:

White Light Output (Normal/Eco):

3,300 lm

Colour Light Output:

3,300 lm

Connectivity:

USB Interface:

USB Type B: 1 (For Firmware Update, Copy OSD Settings)

Analog Input:

D-Sub 15pin: 1

Digital Input:

HDMI: 1

Screen Size (Projected Distance):

Standard Size:

Tele: 22" to 259" [0.87 to 10.34 m]

Wide: 30" to 350" [0.87 to 10.34 m]

Operating Temperature:

Operating Temperature:

Low Altitude: 5 – 40 °C <41 – 104 °F> High Altitude: 5 – 35 °C <41 – 95 °F>

(20% – 80% Humidity, No Condensation)

Operating Altitude:

Operating Altitude:

0 – 3,048 m <0 – 10,000 ft>

Start-Up Period:

Start-Up Period:

Up to 6 seconds, Warm-up Period: 30 seconds

Cool Down Period:

Cool Down Period:

Instant Off

Direct Power On/Off:

Direct Power On/Off:

Yes

Dimension Excluding Feet (W x H x D):

Dimension Excluding Feet (W x H x D):

302 x 77 x 234 mm

Weight:

Weight:

Approx. 2.4 kg

Air Filter:

Type:

High Efficiency Filter

Maintenance Cycle:

6,000 / 12,000 hours^{*3}

Fan Noise:

Fan Noise (Normal / Eco):

37dB / 28dB

Power:

Power Supply Voltage:

100 - 240 V AC $\pm 10\%$, 50/60 Hz

Projectors Facets:

Resolution, Projectors Facets:

XGA

Contrast Ratio, Projectors Facets:

15,000:1

Brightness Range Lumens, Projectors Facets:

2000

Features, Projectors Facets:

Quick Corner

Laser / Lamp, Projectors Facets:

Lamp

Specifications of Main Parts:

LCD:

Native Resolution: XGA (1024 x 768)

Size: 0.55" (C2fine)

Lightsource:

Type: 210W UHE

Life (Normal / Eco): 6,000 / 12,000 hours

Aspect Ratio:

4:3

Projection Lens:

Type: No Optical Zoom / Focus (Manual)

F-Number: 1.44

Focal Length: 16.70 mm

Throw Ratio: 1.00 – 1.35 (Digital Zoom)

Zoom Ratio: 1.44 - 1.95 (Wide to Tele)

Copyright © 2023 PT Epson Indonesia. All rights reserved.