

SPECIFICATIONS

Weight –
approx. 1.7 kg / 3.7 lbs. (EMP-1715 / 1705)
approx. 1.6 kg / 3.5 lbs. (EMP-1710 / 1700)



SUPPLIED ACCESSORIES

Power Cable 1.8 m
Computer Cable 1.8 m
USB Cable* 1.8 m
Remote Control With AAA Type Alkaline Batteries x 2pcs

Audio Adapter
Soft Carrying Case
Password Protect Sticker
Wireless LAN Unit with Screw*
EPSON Projector Software for Meeting & Presentation*
User's Manual

*Only for EMP-1715 / 1705

OPTIONAL ACCESSORIES

ELPLP38 (V13H010L38) Replacement Lamp
ELPAF08 (V13H134A08) Air Filter Set
ELPAP02 (V12H005M02) Ethernet Unit

PROJECTION DISTANCE

Diagonal Screen Size (inches)	Wide (cm)	Tele (cm)
30	99	119
40	133	160
60	200	240
80	267	321
100	335	402
200	672	807
300	1009	1211

Multimedia Projector

EMP-1715/1705 EMP-1710/1700

PART NUMBER	V11H228052	V11H231052	V11H230052	V11H232052		
MODEL NUMBER	EMP-1715	EMP-1705	EMP-1710	EMP-1700		
PROJECTION SYSTEM	RGB Liquid-Crystal Shutter Projection System					
SPECIFICATION OF MAIN PARTS	LCD	SIZE DRIVING METHOD PIXEL NUMBER NATIVE RESOLUTION	0.7 Inch with MLA (x 3) Polysilicon TFT Active Matrix 786,632 Dots (1024 x 768) x 3 XGA Manual Focus & 1.2 x Optical Zoom F=1.6 – 1.77 / f=23.8 – 28.5 mm 170 W UHE 2000 Hours (High Brightness Mode) / 3000 Hours (Low Brightness Mode)			
	PROJECTION LENS					
	LAMP	TYPE LIFE*				
*These are not the guaranteed number of lamp hours, but the recommended hours after which the lamp should be replaced in order to ensure optimum picture quality						
SCREEN SIZE (PROJECTED DISTANCE)	30 to 300 Inch (1.0 to 12.1 m)					
BRIGHTNESS	HIGH BRIGHTNESS MODE LOW BRIGHTNESS MODE	2700 ANSI lm 2100 ANSI lm	2200 ANSI lm 1700 ANSI lm	2700 ANSI lm 2100 ANSI lm 2200 ANSI lm 1700 ANSI lm		
CONTRAST	400:1</					