## Hite Pro 700X





Display Type

1 x DLP Chip

1500

XGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast

φ500 Lux (bei 200 cm Screen) creen

Black Level Offset

> XGA 1024 x 768 786.432 Pixel PAL, SECAM, NTSC

Video Modes Application

Focus

Zoom

Resolution

Standard-Portabel | External training and company presentations, as well as product presentations.

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

Operating Costs -

Objective

Throw Ratio

Audio

Connections Ceiling Mounting Power Size WxHxD

Operating Noise -

Lux:500 Lux Room light max.:100 Lux Candela pro m<sup>2</sup>:158 cd/m<sup>2</sup> Foot-Lamberts:46 fL 4/3 screen width:200 cm Screen:1 Gain

Weight 1,50 kg / 3,31 lbs.

Keystone Illumination

Frequenz

Foot-Lamberts 46 fL / max. 337 cm screen width

158 cd/m<sup>2</sup>

**Features** 

Status Data

More Details

- Discontinued (EOL) // Last update of the data: 2023-08-04



https://www.projector-database.com/pro/hitpro700x-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.