

InFocus IN114xa

INFOCUS IN114XA



Brief Introduction

Beta 2.5

Display Type



1 x 0,55" DLP Chip
XGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level Offset

Projector	3500 / 2800 im Eco Mode	Screen	1167 Lux (bei 200 cm Screen)
	18000:1 full on/off		18000:1 full on/off
	0,1944 min. Lumen		0,065 min. Lumen

Resolution

XGA 1024 x 768
786.432 Pixel

Video Modes

WUXGA 1920 x 1200 compressed
Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 3D, EDTV 480p, 576p
Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom
Frame Sequential (3D Ready)

3D Compatibility

Standard-Portabel | External training and company presentations, as well as product presentations.

Application

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source

195 / 160W im Eco Mode Lamp

Light Life

Articel Nr.: SP-LAMP-097

5000 h. 6000 h. in Eco Mode

Operating Costs

-

Focus

Manual

Zoom

Manual 1,1

Objective

-

Throw Ratio

1,95-2,15:1

Audio

3W Mono

Connections

HDMI 1.4b in
2 x D-sub 15 pin in 1 x out
S-Video in
Cinch Video in
RS232C
Mini Jack Audio in und out



