



DLA-VS2200G

Visualization Series D-ILA Projector
(Interchangeable Lens Version)

Low Cost of Ownership!

*Digital Smear Reduction
w/Black Frame Insertion*

*1920x1080
Native Resolution*

*High Dynamic Range
18,000:1 Native Contrast*



● Features

- 1920 x 1080 Native Resolution
- 3 Active Matrix, 0.7" Digital D-ILA Devices
- >18,000:1 Contrast Ratio (minimum)
- Digital Smear Reduction via Black-frame Insertion
- 23ms Frame Delay
- 1080p60/50 Synchronous Operation
- 850 ANSI Lumens (minimum)
- 12-Bit Gamma Correction
- 7-Axis Color Management System
- 4000 hour, 230W Ultra High Pressure Lamp for Low Operating Cost
- Rugged Chassis for Motion-Base Applications
- 8 Step Lamp Aperture Control
- Sim Specific D-ILA Devices
- High Contrast IR output for stimulated NVG applications
- User Adjustable Gamma Tracking
- Long-life Wiregrid Polarizers
- Long-life Inorganic Optical Components
- Available 1.0:1 and 1.2:1 Fixed Lenses
- $\pm 50\%$ V Offset, $\pm 25\%$ H Offset
- Flexible Orientation- ± 90 Deg. Pitch, ± 10 Deg. Roll
- 11x11 Matrix, 1/16 pixel Micro-Convergence Control
- Comprehensive LAN/RS232 Control Protocol
- Configuration Save/Restore Capability

Specifications

Image Device			3 HD-ILA® devices (0.7 inches diagonal) >90% Aperture Ratio
Brightness			850 ANSI Lumens (minimum)
Resolution			1920x1080 Pixels (16:9 Aspect Ratio)
Contrast Ratio (Sequential)			18,000:1 minimum, 30,000:1 typical
Uniformity			Greater than 80%
Aperture			8 Steps (Lamp Aperture)
Gamma Control			Std 2.2 Gamma and 6 User adjustable Gamma presets
Color Management			7-Axis adjustable CMS
HDMI Input - Supported Formats			1920x1080 (EDID for 1080p60, 1080p50 only)
Low Latency Mode			1080p60/50
Latency			23ms w/1080p60 Input
Color Bit Depth			10-bit Input via HDMI 1.4a, 10-bit display
I/O Terminals			2 x HDMI v1.4a (locking HDMI connectors) LAN, RJ45 x 1 RS-232C, D-Sub 9 pin (male) x 1 Wired Remote (Mini) x 1
Remote Control			RS-232C/LAN Fully featured control protocol Wired/IR Remote Control
Available Lenses and Accessories			1.0:1 and 1.2:1 Fixed Lens ± 50% Vertical Offset, ± 25% Horizontal Offset Capability Fixed Offset Lens mounts available (standard and custom)
Lamp (user replaceable)	PK-L2313UP		230W Ultra High Pressure Type (170W Low, 230W High) 4000 hour nominal life to 50% brightness (Low Power Setting)
Power Requirement			AC 100V-240V, 50/60Hz
Power Consumption			360 Watts Maximum, 7W Standby
Noise Level (0-26°C, 32-79°F)			<35dB (A) at 39.4"/1m (3.3ft)
Operating Environment			Temperature range 5°C-35°C Humidity 20%-80% (non-condensing)
Operating Altitude			<1500 meters for guaranteed performance
Installation Orientation			Vertical ±90 degrees, Horizontal ±10 degrees
Dimensions (W x H x D)			17-15/16" x 7-1/16" x 18-5/8" (455 x 179 x 472mm)
Weight			34lbs, (14.6kg)
Supplied Accessories			English Instruction Manual Power Cord
Approvals	Safety	North America	CSA C22.2 No.60950-1-03, UL60950-1
		Europe	IEC60950-1 (EU)
	EMI	North America	FCC part 15 Class B(US), ICES-003 Issue 4, 2004(CAN),
	Europe		EN61000-3-2, EN61000-3-3, EN61000-6-3
	Environmental	Australia	AS/NZS CISPR 22:2004 Class B
		Common	RoHS
		North America	Proposition 65 (US), Mercury Regulation
			WEEE New Battery directive
Warranty			Two Years Parts and Labor (per JVC Limited Warranty)



JVCKENWOOD

D-ILA is a trademark of JVCKENWOOD Corporation
E.&O.E., Design and specifications are subject to change without notice.
All brand names and product names are trademarks, registered trademarks, or trade names
of their respective holders.

Copyright 2015, JVCKENWOOD Corporation
All rights reserved

Rev 3.10.15