

Kindermann omega SX 1280

KINDERMANN OMEGA SX 1280

Brief Introduction

Beta 2.5

A brief introduction to the Kindermann omega SX 1280. The LCD projector has an SXGA 1280 x 1024 resolution and a contrast of 150:1. 300 Ansi lumens ensure that a picture width of 147 cm is also possible. However, if room light is available, the picture should be max. 98 cm wide. On the market since 1997, the model is no longer offered by the manufacturer Kindermann.



LCD TFT Panel
SXGA 5/4 Liquid Crystal Display

Display Type

Ansi-Lumen

Contrast

Black Level
Offset

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting

Power

Size WxHxD

Operating Noise

300

150:1 full on/off

2,0000 min. Lumen

SXGA 1280 x 1024

1.310.720 Pixel

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Very narrow picture width and rooms with very little light.

575W Metalldampf Lamp

1000 h.

-

Manual

Manual 1,11

f=303-335 mm

-

2 x 10W

-

-

750W

366 x 310 x 660 mm (14,4"x12,2"x26") 74,88 L/dm³

-

18,50 kg / 40,79 lbs.

-

-

H-sync: 30-80 kHz

V-sync: 50-100 Hz

Range max.: 150 MHz

9 fL / max. 147 cm screen width

31 cd/m²

-

Features

Screen Mirroring

Optional only Chromecast / Fire TV / Apple TV / Mi Box Ads

Optional accessories



Luftfilter universal

uni3mm

18,15 €

Status

Data

1997 Discontinued (EOL) // Last update of the data: 2026-06-09

More Details



HCinema

<https://www.projector-database.com/pro/kindermannomegasx1280-en.html>

