Lenovo TD120







Brief Introduction

Beta 2.5

Display Type

Black Level

Resolution

Offset

2000 Ansi lumens. In room light, however, the image width should ideally be less than 259 cm. It is no longer offered by the manufacturer Lenovo. 1 x 0,55" 12° DDR DLP Chip SVGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast

2000

1600:1 full on/off 1,2500 min. Lumen

SVGA 800 x 600

480.000 Pixel

SXGA 1280 x 1024 compressed

Video Modes PAL, SECAM, NTSC

Standard-Portabel | External training and company presentations, as well as product

800 x 600 resolution. The projector can illuminate a picture width of up to 389 cm thanks to the

φ647 Lux (bei 203 cm Screen)

0.405 min. Lumen

presentations. Application

Medium screen width or rooms with little light, max. 100 lumens.

Light Source Light Life

200W Lamp 2000 h.

Operating Costs

Focus Manual

Zoom Manual 1,16

Objective

Throw Ratio

Audio

DVI-I

Cinch Video in S-Video in Mini Jack **USB**

RS232C Yes

Ceiling Mounting

Connections

Power

Size WxHxD 280 x 97 x 205 mm (11"x3,8"x8,1") 5,57 L/dm3

Operating Noise

2,10 kg / 4,63 lbs. Weight Keystone Vert.: +/-15° Illumination

90%

H-sync: 15,31-70 kHz Frequenz V-sync: 50-85 Hz

60 fL / max. 389 cm screen width Foot-Lamberts

206 cd/m²

Lux:647 Lux Room light max.:129 Lux Candela pro m²:206 cd/m² Foot-Lamberts:60 fL 4/3 screen width:203 cm Screen:1 Gain

Features Status Data

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.