LG

Digitally yours

DLP PROJECTOR

RD-JT40/41

The new DLP Projector. RD-JT40/41, provides an excellent brightness of 2000 ANSI lumens with true XGA . With an outstanding image quality and brightness, RD-JT40/41 will take you to perfect presentation.

2000 ANSI Lumen & Real XGA

It is easy with us wherever, whenever you go

Size is equal to A4 paper, 7.5lbs(3.1kg) in weight
you can take it anywhere and make a good use of it.

Brightness 2000 ANSI lumens
It presents a very distinct image in lighted indoors.

0101000100110101101101010000101001

DLP PROJECTOR
RD-JT40/41

Specification

Model			RD-JT40	RD-JT41
SPECIFICATION	NATIVE RESOLUTION		XGA	SVGA
	MAX RESOLUTION		SXGA	SXGA
	BRIGHTNESS(ANSI Lumen)		2000	2000
	CONTRAST RATIO		600:1	600:1
	UNIFORMITY		85%	85%
	SIZE(WxHxD, mm)		308 x 95 x 240	308 x 95 x 240
	WEIGHT		3.1Kg	3.1Kg
	NOISE		<34dB	<34dB
	VIDEO COMPATIBILITY		NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM, S-VIDEO	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM, S-VIDEO
	HD READY		1080i & 720p	1080i & 720p
	THROW DISTANCE(m)		0.8 ~ 10	0.8 ~ 10
	IMAGE SIZE		22" ~ 300"	22" ~ 300"
	POWER SUPPLY		AC100 ~ 240V, 50Hz/60Hz	AC100 ~ 240V, 50Hz/60Hz
	POWER CONSUMPTION		330W	330W
LCD/DMD PANEL	SIZE		0.7 DMD™ x 1, XGA	0.7 DMD™ x 1, SVGA
	DISPLAY TYPE		Digital Light Processing	Digital Light Processing
LAMP	TYPE		210W NSH	210W NSH
	LIFE TIME		2000Hr	2000Hr
LENS	ZOOM STYLE		MANUAL	MANUAL
	FOCAL LENGTH(mm)		23 ~ 27.6	23 ~ 27.6
CONTROL	RS-232C		O	O
AUDIO	STEREO		X	X
	OUTPUT		3W	3W
INPUT TERMINAL	PC	PC Input(d-sub)	1	1
		PC sound in	1	1
		USB	1	1
	A/V	S-video	1	1
		A/V Input	1	1
		SBNC(COMPONENT)	1 (Y/Pb/Pr, Y/Cb/Cr)	1 (Y/Pb/Pr, Y/Cb/Cr)
		RCA(COMPOSITE)	1	1
OUTPUT TERMINAL	PC	PC OUTPUT(d-sub)	1	1
		MOUSE PORT	1	1
KEYSTONE	DIGITAL	VERTICAL	±7°	±7°
	MAC DESKTOP ADAPTOR		optional	optional
REMARK			ceiling mount:optional	ceiling mount:optional

Performance

- HD Compatible 1080i, 720p
- Window Zoom
- Low Noise of 34dB
- Digital Keystone Correction
- Picture In Picture (PIP)

Features

- 2,000 ANSI Lumens
- Real XGA / Compressed XGA (SVGA)
- 3.1kg & 308 × 90 × 240mm
- Contrast of 600:1
- 1 × 0.7" DMD Panel
- 210W NSH Lamp

Supplied Accessories

Remote control, Batteries, Power cord, PC cable, A/V cable, S input Cable, PC Audio cable, PS/2 mouse cable, Mac mouse cable, Mac Desktop adapter, Soft Bag

Connector Panel

The RD-JT40/41 enables direct input connection of plural sources via one PC, one S-video and video outputs for NTSC, NTSC4.43, PAL, PAL-M, PAL-N or SECAM and performs automatic frequency adjustment in response to the signal received

LG Electronics Inc.

20 Yoido-dong, Youngdungpo-gu, Yoido P.O Box 335, Seoul 150-721, Korea Tel: +82-2-3777-7574 Fax: +82-2-3777-7575 http://www.lge.com

※ Features and specifications are subject to change without notice.