Luxcine ESP214



တLux (bei 200 cm Screen) ဂ -ဓ -





Display Type

Resolution

1 x LCD TFT Panel

SVGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast 600:1 full on/off

Black Level

Offset

SVGA 800 x 600 480.000 Pixel

XGA 1024 x 768 compressed

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product presentations. Application

Very narrow picture width and rooms with very little light.

Light Source **LED** 20000 h. Light Life Operating Costs 0,00 € LED

Focus Manual

Zoom No Zoom

Objective F=1,44 f=16,6mm

Throw Ratio

Audio

D-sub 15 pin in

YUV in

Cinch Video in Connections

USB in

SD-CARD slot

Cinch Stereo in und out

Ceiling Mounting

Power 80W

Size WxHxD

230 x 127 x 320 mm (9,1"x5"x12,6") 9,35 L/dm3

Operating Noise 28dB

Weight 3,80 kg / 8,38 lbs. Vert.: +/-12° Keystone

Illumination

Frequenz

Foot-Lamberts

Features

Status

2009 Discontinued (EOL) // Last update of the data: 2023-09-07

Data

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.