DLP™ PROJECTOR



Marantz is proud to introduce a new Home Theater projector, the VP8600. This projector is designed to reach a new low price point to open up a completely different customer who might have been only able to aspire to own a Marantz video projector in the past. Not only have we made it more affordable to purchase, with a lamp life of 4000 hours we have drastically cut the cost of ownership as well. And with a fan noise of only 27 dB, if you weren't seeing an amazing picture on the screen, you would never know it was on!

- Texas Instruments DLP™ (Digital Light Processing) Technology
- High Definition (1280 x 720) HD2+ DMD™ system
- >2500:1 Contrast Ratio
- 800ANSI Lumen Brightness
- x1.33 Zoom Range
- 10 Bit Digital Gamma Processing
- Up: 50% to 120% Lens Shift Range
- DVI (with HDCP) Input

- 4000 Hours Long Life 200W VIP Lamp
- H/V Keystone Collection
- Motion Adaptive Deinterlacing
- White Peak Enhance Mode
- PIP (Picture In Picture)
- Dual Component Inputs (3RCA/5BNC)
- RS232C Connection for System Control
- x2 Trigger Outputs
- Backlit Remote















FEATURED OPTICS	DMDTM (TLDLDTM Tackgalage) LIDC
Display Device	DMD TM (TI DLP TM Technology) HD2+
Panel Size	0.81"
Aspect Ratio	16:9
Resolution	1280x720
Brightness	800 ANSI Lumen
Brightness Uniformity	90%
Contrast Ratio	2500 : 1
Projection Size	40" - 300"
Throw Distance 100" (16:9)	
TV System	NTSC, PAL, SECAM
Computer Signal Capability	VGA, SVGA, XGA, SXGA
DTV / HDTV Capability	480i, 480p, 720p, 1080i
Video Processor	Original
3:2 Pull Down	•
Optics	Custom optics
Life Lamp	4000 hours (average)
Picture Memories	 (By Input and signal)
Keystone Correction	• (H/V)
Fine Picture Menu	•
Picture Modes Low	Bright, Theater, Standard, Dynamic, High Bright
Color Temperatures	• (4 steps)
Black Level Selection	•
Optical Zoom	• (x1.33)
Lens Shift	• (V: +50% - +120%)
Dust-Free Sealed Optics	•
Noise cancel Structure	•
Chassis	Extruded Aluminum
Illuminated I/O Terminal Par	nel •
Auto Color Temp. Calibration	1 •
FCC	Class B

IN/OUTPUTS		
VIDEO		
Composite Video In	1	
S-Video In	1	
Component In	2 (RCAx3, RCAx5)	
RGB/HD In	1 (D-Sub 15pin)	
Digital Video In	1 (DVI w HDCP)	
OTHERS		
D-Bus Remote (RC-5) In/Out	-	
External Control (RS232C)	•	
DC Trigger Out	2 (3.5 mm mini jacks)	

GENERAL	
Color	Black or Silver
Remote Control	Backlit Device Remote RC8600VP
Power Requirement	AC 100-240 V, 50/60 Hz
Power Consumption	255 W
Dimensions W x H x D (Inches)	17 1/8" X 7 1/2" X 15 3/16"
Weight (lbs)	26.4



*All specifications, dimensions and weights are subject to change without notice. D&M Holdings, Marantz, Marantz America, Inc. or any of its subsidiaries will not assume any liability for errors in this full line catalog which may result in consequential errors being made by retail dealers, designers, custom installers, cabinet makers or end users, etc based upon information contained within this document.

