## marantz

**VP8600 DLP Projector** 



Marantz is proud to introduce a new Home Theater projector, the VP8600. This projector brings the remarkable Marantz quality and excellence to those who, in the past, may have only aspired to own a Marantz video projector. Not only have we made it more affordable to purchase, with a lamp life of 4000 hours we have drastically cut the cost of ownership as well. And with a fan noise of only 27 dB, if you weren't seeing an amazing picture on the screen, you would never know it was on!

- Texas Instruments DLP™ (Digital Light Processing) Technology
- High Definition (1280 x 720) HD2+ DMD $^{\text{TM}}$  system
- >2500:1 Contrast Ratio
- 800ANSI Lumen Brightness
- x1.33 Zoom Range
- 10 Bit Digital Gamma Processing
- Up: 50% to 120% Lens Shift Range
- DVI (with HDCP) Input

- 4000 Hours Long Life 200W VIP Lamp
- H/V Keystone Collection
- Motion Adaptive Deinterlacing
- White Peak Enhance Mode
- PIP (Picture In Picture)
- Dual Component Inputs (3RCA/5BNC)
- RS232C Connection for System Control
- x2 Trigger Outputs
- · Backlit Remote











## **VP8600**

VP8600	
FEATURED OPTICS	
Display Device	DMD <sup>TM</sup> (TI DLP <sup>TM</sup> Technology) HD2+
Panel Size	0.81"
Aspect Ratio	16:9
Resolution	1280x720
Brightness	800 ANSI Lumen
Brightness Uniformity	90%
Contrast Ratio	2500 : 1
Projection Size	40" - 300"
Throw Distance 100" (16:9)	158" - 208"
TV System	NTSC, PAL, SECAM
Computer Signal Capability	VGA, SVGA, XGA, SXGA
DTV / HDTV Capability	480i, 480p, 720p, 1080i
Video Processor	Original
3:2 Pull Down	•
Optics	Custom optics
Life Lamp	4000 hours (average)
Picture Memories	<ul> <li>(By Input and signal)</li> </ul>
Keystone Correction	• (H/V)
Fine Picture Menu	•
Picture Modes	Low Bright, Theater, Standard, Dynamic, High Bright
Color Temperatures	• (4 steps)
Black Level Selection	•
Optical Zoom	• (x1.33)
Lens Shift	• (V: +50% - +120%)
Dust-Free Sealed Optics	•
Noise cancel Structure	•
Chassis	Extruded Aluminum
Illuminated I/O Terminal P	anel -
Auto Color Temp. Calibration	on •
FCC	Class B

Silver
Backlit Device Remote
RC8600VP
AC 100-240 V, 50/60 Hz
255 W
17 1/8" X 7 1/2" X 15 3/16"
26.4

IN/OUTPUTS		
VIDEO		
Composite Video In	1	
S-Video In	1	
Component In	2 (RCAx3, RCAx5)	
RGB/HD In	1 (D-Sub 15pin)	
Digital Video In	1 (DVI w HDCP)	
OTHERS		
D-Bus Remote (RC-5) In/Out	-	
External Control (RS232C)	•	
DC Trigger Out	2 (3.5 mm mini jacks)	

\*All specifications, dimensions and weights are subject to change without notice. D&M Holdings, Marantz, Marantz America, Inc. or any of its subsidiaries will not assume any liability for errors in this full line catalog which may result in consequential errors being made by retail dealers, designers, custom installers, cabinet makers or end users, etc based upon information contained within this document.

