

EX632P

- Native XGA – for detail & clarity
- Exceptional brightness – 3,500 ANSI Lumens
- Up to 6,000 hours lamp life
- Crestron RoomView® – RJ45 control and monitoring



Stylish yet easy to use, the EX632P is a great XGA multi-functional projector.

Impressive 3,500L with technology brings to life business presentations, video graphics and movies on the big screen.

Designed with you, the presenter, in mind, the EX632P incorporates extensive connectivity, powerful 10W stereo speakers and Crestron RoomView control to maintain and monitor the projector over the network. The environmentally friendly EX632P has energy saving features including <0.5W standby mode and auto power off saving you both time and money.

SPECIFICATIONS

Display Technology	Single 0.55" XGA DC3 DMD chip DLP™ Technology by Texas Instruments
Native Resolution	XGA 1024×768
Brightness1(Bright Mode)	3,500 ANSI Lumens
Contrast	10,000:1
Noise Level (Eco mode)	25dB
Weight (kg)	2.8
I/O Connectors	HDMI, 2× VGA (RGB/YpPr), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232
Preset Mode	Maximum contrast and Colour accuracy sRGB: Best Colour Reproduction User: Memorises user's settings Presentation Default mode, perfect with computers or notebooks Bright For environments with high ambient light (Brightest image) Blackboard Perfect for installations with blackboards
Maximum Resolution	UXGA 1600×1200
Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Video Compatibility	PAL(B, D, G, H, I, M, N, 576i/p), NTSC(M, 4.43/3.58 MHz, 480i/p), SECAM(B, D, G, K, K1, L), HD(1080i, 720p)
Displayable Colours	1.07 Billion
Projection Lens	F/2.54~2.78; f=18.36~22.02mm, 1.2× Manual Zoom
Throw Ratio	1.6 - 1.9:1
Projection Screen Size	0.78 - 9.38m (30.79" - 369.43") Diagonal 4:3
Projection Distance	1.2 - 12m
Zoom Type	1.2× Manual
Aspect Ratio	4:3 Native, 16:9/16:10 Compatible
Offset	115% ±5%
Horizontal Scan Rate	15 - 105kHz
Vertical Scan Rate	50 - 128Hz
Lamp Life (Eco/Bright Mode)	6,000/3,500
Keystone Correction	± 20° Vertical
Audio	10W
Dimensions (W x D x H) (mm)	318×224×102
Remote Control	Control Full function remote
Power Supply	100-240V, 50-60Hz
Power Consumption	280W BRIGHT mode < 0.5W Standby mode, 225W Eco+ mode < 0.5W Standby mode
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Uniformity	70%
Security	Kensington Lock, Password Protection
Standard Accessories	AC Power Cord, VGA Cable, Infra Red Remote Control with Batteries, CD User Manual
Optional Accessories	Ceiling Mount Kit
RoHS	Compliant
Speaker	10
On Screen Display	On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Arabic
Optional Wireless	Optional Wireless No

*The appearance and specifications of all item are subject to change without notice

Optoma Corporation

12F., No.213, Sec. 3, Beixin Rd.,

Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: +886 2 8911 8600 Fax: +886 2 8911 6550

<http://asia.optoma.com>