



Key Features

- Easy-to-read text – bright at 3500 ANSI lumens and high 3000:1 contrast ratio
- VGA and audio pass-thru operational on standby mode
- Filter-free design means lower cost of ownership
- Remote management via RS-232 or RJ45 connectivity
- Broad range of audio and video connectivity
- Wireless connectivity with optional dongle

Detail Specifications

Display Technology

Single 0.55" DMD DLP Technology by Texas Instruments

Resolution

Native XGA (1024x768)

Maximum Resolution

UXGA (1600x1200)

Contrast Ratio

3000:1 (Full On/Full Off)

Lamp Life and Type

4000/3000 Hours (STD/Bright)
230W P-VIP

Throw Ratio

1.95 to 2.15:1 (Distance/Width)

Projection Distance

3.93' to 39.3' (1.2 to 12m)

Image Size (Diagonal)

27.5" to 303" (0.7 to 7.69m)

Aspect Ratio

4:3 Native, 16:9 and 16:10
Compatible

Audio

Two 5-Watt Stereo Speakers

Remote Control

Fully Featured IR Remote with
Laser Pointer and Mouse

Operating Temperature

41 to 104°F (5 to 40°C), 80%
Max Humidity

Power Supply

AC Input 100-240V, 50-60Hz,
Auto-Switching

Power Consumption

328 Watts (Bright), 272 Watts
(STD) <1 Watt (Standby)

Warranty

3 Years Optoma Express
Replacement Service, 1 Year on
Lamp

Standard Accessories

AC Power Cord, VGA to VGA
Cable, USB Cable, Remote
Control, Batteries for Remote,
Carrying Case, Lens Cap,
CD-ROM User's Manual, Quick
Start Card and Warranty Card

Optional Accessories

Ceiling Mount, Wireless Dongle,
HDMI Cable, VGA to
Component Cable, S-Video
Cable, Composite Video Cable,
RS-232 Cable and Panoview™
Series Screens

UPC

796435 41 130 5