PREMIER

PRODUCT CATALOG

PROJECTOR DLP SERIES

OPTICS IN FOCUS

PROJECTOR DLP SERIES

PD-X702

Whether you're in the boardroom, the classroom, or on the road, this powerful, easy-to-use projector can help you make presentations more professional with confidence.

- XGA native resolution (1024 x 768)
- 3000 ANSI Lumens for extremely bright projection
- 2000:1 contrast ratio

PD-X712

Whether you're in the boardroom, the classroom, or on the road, this powerful, easy-to-use PD-X712 can help you make presentations more professional with confidence.

- XGA native resolution (1024 x 768)
- 3200 ANSI Lumens for extremely bright projection
- 2000:1 contrast ratio
- TI DDP3020

PD-X/S611

For brilliant, fill-featured performance at an extraordinary, Premier PD-X/S611 offer the ideal solution.

- XGA/SVGA native resolution
- 2000 ANSI Lumens brightness
- 2000 : 1 contrast ratio

PD-X/S621

Premier 's 2000 lumens PD-X/S621 multi-media projector, makes a wide range of environments from boardrooms to classrooms. Compact and portable DLP multi-media projector.

- XGA/SVGA native resolution
- 2000 ANSI Lumens brightness
- 2000 : 1 contrast ratio
- D-sub In / Out

PD-X631

Premier 's 2500 lumens PD-X631 multi-media projector, makes a wide range of environments from boardrooms to classrooms. Compact and portable DLP multi-media projector.

- XGA native resolution (1024 x 768)
- 2500 ANSI Lumens brightness
- 2000:1 contrast ratio
- D-sub In / Out

PD-X770

PD-X770 gives you a light-weight, super compact size and bright mobile projector. Its XGA native resolution delivers you a wonderful viewing experience. Furthermore, light-weight and super compact size give you excellent mobility in business.

- XGA native resolution (1024 x 768)
- 1800 ANSI Lumens brightness
- 2000:1 contrast ratio
- Weight : 2lb. (1.18kg)

PD-S690

With ultraportable, superior image quality, and easy-to-operate features, the LED lightsource PD-S690 no doubt is your best choice to present personal digital camera images and urgent business documents anywhere and anytime.

- SVGA native resolution (800 x 600)
- 2.5 hours battery operation
- 12" - 60" wide focus range
- SD card slot

HE-W721

With an HDTV-capable resolution of 1,280 x 768 pixels in 16:9 widescreen format and outstanding contrast ratio of 2000:1, HE-W721 lets you enjoy your favorite movies and sports on a big screen in your own home or play life-sized video games.

- 16:9 format native 1280x768 resolution
- 1500 ANSI Lumens brightness
- 2000 : 1 contrast ratio
- HDMI built in
- TI DDP3020

PROJECTOR DLP SERIES

Premier model	PD-X702	PD-X712	PD-X/S611	PD-X/S621	PD-X631	PD-X770	PD-S690	HE-W721
Picture								
Display Type	0.7" XGA DDR DMD	0.7" XGA DDR DMD	0.55" XGA/SVGA DDR DMD	0.55" XGA/SVGA DDR DMD	0.55" XGA DDR DMD	0.7" XGA DDR DMD	0.55" SVGA DDR DMD	0.65" WXGA DDR DMD
Resolution (Pixels)	XGA (1024 x 768)	XGA(1024 x 768)	XGA (1024 x 768) SVGA (800 x 600)	XGA (1024 x 768) SVGA (800 x 600)	XGA(1024 x 768)	XGA(1024 x 768)	SVGA(800 x 600)	WXGA(1280 x 768)
Brightness(ANSI Lumens)	3000	3200	2000	2000	2500	1800	30	1500
Uniformity	80%	80%	80%	80%	85%	80%	85%	85%
Lens	Manual Zoom (1.2x)	Manual Zoom (1.2x)	Manual Zoom (1.2x)	Manual Zoom (1.2x)	Manual Zoom (1.15x)	Manual Zoom (1.16x)	Fixed Zoom	Manual Zoom (1.12x)
Contrast ratio	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	500:1	2000:1
Screen Size	30 - 300 inches	30 - 300 inches	31.2 ~ 312 Inches / 27.8 - 277.7 inches	31.2 ~ 312 Inches / 27.8 - 277.7 inches	24.8 ~ 285.7 Inches	40 ~ 273 Inches	12 ~ 60 Inches	37.5 ~ 250 Inches
Lamp	250W	270W	250W	205W	230W	150W	NA	230W
Lamp Life	2000 hours	2000 hours	2000 hours	2000 hours	2000 hours	3000 hours	10,000 hours	2000 hours
Color Wheel	4 Segment RGBW	4 Segment RGBW	4 Segment RGBW	4 Segment RGBW	4 Segment RGBW	4 Segment RGBW	3 LED type	6 Segment RGBW
Keystone Correction	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees
Audio System	2W x 1	2W x 1	2W x 1	2W x 1	2W x 1	1W x 1	0.3W x 1	2W x 1
Video Signals	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM	NTSC PAL - 60, M, N, B, D, G, H,I SECAM
Computer Input	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin
Computer Output	D-Sub 15 pin	D-Sub 15 pin	NA	D-Sub 15 pin	D-Sub 15 pin	NA	NA	NA
Video Input	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub, DVI	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub, HDMI
Audio Input	Mini Jack	Mini Jack	Mini Jack	Mini Jack	Mini Jack	Mini Jack	Mini Jack	Mini Jack
Control Input	USB	USB, RS232	USB	USB, RS232	USB, RS232	USB, RS232	NA	USB, RS232
Sound Noise	36dBA	36dBA	32dBA	34dBA	34dBA	34dBA	30dBA	33dBA
Power Requirement	100 - 240v, 50 - 60Hz	100 - 240v, 50 - 60Hz	100 - 240v, 50 - 60Hz	100 - 240v, 50 - 60Hz	100 - 240v, 50 - 60Hz	100 - 220v, 50 - 60Hz	100 - 220v, 50 - 60Hz	100 - 240v, 50 - 60Hz
Power Consumption	300W	325W	250W	250W	300W	200W	40W	280W
Dimension (WxDxH)	290 x 220 x 95 mm	290 x 220 x 95 mm	256 x 220 x 88 mm	265 x 202 x 97 mm	265 x 202 x 97 mm	201 x 155 x 58 mm	121 x 99 x 47 mm	106 x 287 x 220.5 mm
Weight	3.0Kg (=6.6lbs.)	3.0Kg	2.1Kg	2.4Kg	2.4Kg	1.18Kg	345g	3.0Kg
Standard Accessory	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Power cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1	Remote Control with 2 batteries Power cable x 1 D-Sub to D-sub cable x 1 Audio cable x 1 / S-video x 1 Composite video x 1 Operating manual x 1 Carrying bag x 1

Specifications are subject to change without notice.

Our Focus Reflects Our Passion for Perfection

普立爾科技股份有限公司
PREMIER IMAGE TECHNOLOGY CORPORATION
No. 32, Ji-Hu Rd, Nei-Hu, Taipei 114. Taiwan, ROC
Tel : +886-2-2799-6111 Fax : +886-2-2799-8284
www.premierimage.com.tw
04639-6013-00

PREMIER

© 2006 Premier Image Technology Corporation All rights reserved.
Corporate names and trademarks are the porperty of their respective companies.
Specifications are subject to change without notice.