## P D X 7 0

## **Premier PD X702**





**Brief Introduction** Beta 2.5

1 x 0,7" DLP Chip

Display Type

Ansi-Lumen Contrast Black Level Offset

Resolution

Video Modes

Application

Light Source

Light Life **Operating Costs** 

Focus

Zoom

Objective Throw Ratio

Audio

Connections

Ceiling Mounting Power Size WxHxD

Operating Noise

resolution and a contrast of 2000:1. 3000 Ansi lumens ensure that a picture width of 477 cm is also possible. However, if room light is available, the picture should be a maximum of 318 cm wide. On the market since 2005, the model is no longer offered by the manufacturer Premier.

დ1000 Lux (bei 200 cm Screen)

2000:1 full on/off 0,501 min. Lumen

XGA 4/3 Ti Digital Light Processing Chip

3000 2000:1 full on/off

1,5000 min. Lumen

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

2000 h.

Manual

Manual 1,2

1 x 2W

D-sub 15pin in S-video in Cinch Video in

Yes 300W

290 x 95 x 220 mm (11,4"x3,7"x8,7") 6,06 L/dm3

34dB

Lux:1000 Lux Room light max.: 200 Lux Candela pro m<sup>2</sup>:319 cd/m<sup>2</sup> Foot-Lamberts:93 fL 4/3 screen width:200 cm Screen:1 Gain

3,00 kg / 6,61 lbs. Weight Vert.: +/-15° Keystone

80% Illumination

Frequenz

Foot-Lamberts 93 fL / max. 477 cm screen width

319 cd/m<sup>2</sup>

**Features** 

Status

2005 Discontinued (EOL) // Last update of the data: 2023-08-04

Data









Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.