

projectiondesign F3 SXGA+



With the F3 SXGA+, manufacturer projectiondesign offers a DLP projector with SXGA+ 1400 x 1050 resolution and a contrast of 7500:1. The projector also offers a lens shift function that makes image adjustment childs play. 646 cm image width, the projector will be able to illuminate well. The projector can create rooms with residual light with a smaller image width, we would recommend a maximum of 431 cm here. With only 30 decibels of operating noise, the model is already very quiet compared to others. The model built in 2004 is no longer offered by projectiondesign.

 1 x 0,95" LVDS DC2 DLP Chip
SXGA 4/3 Ti Digital Light Processing Chip

Projector 5500 - 1000 stufenlos regelbar
7500:1 full on/off
0,7333 min. Lumen

Screen 1833 Lux (bei 200 cm Screen)
7500:1 full on/off
0,244 min. Lumen

Vert.: +/-55% Hori.: +/-45% motorisch
SXGA+ 1400 x 1050

Resolution 1.470.000 Pixel

UXGA 1600 x 1200 compressed

Video Modes PAL, SECAM, NTSC, EDTV HDTV 720p, 1080i,

Application Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Wide screen width or rooms with plenty of light (over 200 lumens).

Light Source 2 x 250W UHP Lamp

Light Life Articiel Nr.: 400-0300-00

2000 h. 4000 h. in Eco Mode

Operating Costs 22,26% / 0,73 €

Focus Powered


Zoom Powered

Objective optional

Throw Ratio optional

Audio -

Connections DVI-D mit HDCP
D-sub 15pin in und out
5 x BNC RGBHV
YUV
Cinch Video in
S-Video in



Brief Introduction
Beta 2.5

Display Type

Ansi-Lumen

Contrast

Black Level

Lens shift

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio


Connections

Mini Jack
USB
RJ45 Hub
RS232C Din 9pin



Ceiling Mounting Yes
Power 900W
Size WxHxD 507,3 x 218,3 x 375,4 mm (20"x8,6"x14,8") 41,45 L/dm³
Operating Noise 30dB

Weight 15,00 kg / 33,07 lbs.
Keystone Vert.: +/-30°
Hori.: +/-15°
Illumination -
Frequenz H-sync: 15-150 kHz
V-sync: 48-190 Hz
Range max.: 205 MHz
Foot-Lamberts 170 fL / max. 646 cm screen width
582 cd/m²



- Lens shift Funktion motorisch
- Eco Mode
- Gamma correction
- Dynamic iris
- Digital image shift
- 24/7 continuous operation capable
- Remote control with laser pointer und mouse control
- Lan network compatible.
- Faroudja DCDi with pull down colour wheel with options:
 - - 3-segment 3x graphics, visualisation and simulation
 - - 4-segment 2x graphics
 - - 4-segment 2x high brightness

Optional	Bulb only	NLMP5064
	Lamp ruby	Ruby-LMP5064
	Lamp original	R9801272 / 400-0400-00 / 400-0500-00
	Compatible lamp	LMP-K15468
	Object lens original	R9801209 / EN14
	Object lens original	R9801214 / EN11
	Object lens original	R9801218 / EN12
	Object lens original	R9801225 / EN15
	Object lens original	R9801228 / EN13
	Object lens original	R9801249 / EN16
	Ceiling Mount 220	Halterung45

Order here: <https://www.hcinema.de/lampen/shop-en.php?id=n15557>

Optional Lenses					
Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
projectiondesign EN16	4.1-7.1:1	8.2-14.2 m	+/-55%	+/-45%	Powered
projectiondesign EN14	2.56-4.1:1	5.1-8.2 m	+/-55%	+/-45%	Powered
projectiondesign EN13	1.3-1.7:1	2.6-3.4 m	+/-55%	+/-45%	Powered
projectiondesign EN11	1.7-2.5:1	3.4-5 m	+/-55%	+/-45%	Powered
Fix Optional Lenses					
projectiondesign EN15	1.2:1	2.4 m	+/-55%	+/-45%	No Zoom
projectiondesign EN12	0.8:1	1.6 m	0.0% Fix		No Zoom
Status	2004 Discontinued (EOL) // Last update of the data: 2023-08-04				

Data



More Details



HCinema

<https://www.projector-database.com/pro/projectiondesignf3sxgaplus-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.