

PLC-XU37/XU32

XGA Ultraportable Multimedia Projectors



OPTIONAL WIRELESS IMAGER KIT

An optional Wireless Imager kit allows for the direct capture, compression, and transfer of any software program data, including animated PowerPoint presentations, from a PC to the projector through a wireless LAN module.

OPTIONAL MEDIA CARD IMAGER KIT

An optional Media Card Imager kit with a detachable Presentation Viewer allows for the storage and playback of a JPEG file slideshow without the need for a PC to be attached.

COMPONENT VIDEO INPUTS

Component video inputs and a newly developed Digital RGB Matrix IC make projection of DVD (Y/Cb/Cr) and HDTV (Y/Pb/Pr) possible.

HDTV COMPATIBLE

The PLC-XU37/XU32 is High Definition Television Compatible, accepting the 1080i, 1035i, 720p, 575p, 575i, 480p and 480i HDTV resolution standards.

DIGITAL KEYSTONE CORRECTION

Sanyo's new X-Y digital keystone correction compensates for angled projector placement in both the vertical and horizontal plane.

WHISPER QUIET FAN

The PLC-XU37/XU32 employs a new Whisper Quiet fan that produces minimal background noise.

SANYO

PRESENTATION TECHNOLOGIES

21605 Plummer Street
Chatsworth, CA 91311

Ph: 818.998.7322 ext. 288

Fax 818.717.2719

www.sanyolcd.com


Specifications

| | |
|-----------------------------|--|
| Resolution | XGA (1024 x 768) |
| Brightness (typical) | PLC-XU37 - 2000 ANSI Lumens PLC-XU32 - 1700 ANSI Lumens |
| Uniformity | 85% |
| LCD Panel System | 0.9" TFT Poly x 3 |
| Number of Pixels | 2,359,296 (786,432 x 3) |
| Contrast Ratio | 350:1 (Full on/off) |
| Projection Image (diagonal) | 31"-300" |
| Aspect Ratio | 4:3 |
| Throw Distance | 5.2'-40' |
| Zoom/Focus | Powered (1:1.3 zoom) |
| Up/Down Ratio | 9:1 |
| Digital Keystone Correction | Vert. +/- 20°, Horiz. +/- 10° |
| Projection System | Polarized Beam Splitter optical system |
| Projection Lens | F1.7-2.0 / f1.47"-1.9" |
| Lens Throw Ratio | 2.0-2.6:1 |
| Projection Lamp | 200W UHP |
| Scanning Frequency | H 15-100kHz; V 50-100Hz |
| Dot Clock | 140 MHz |
| Color System | PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43 |
| Computer Compatibility | SXGA, XGA, SVGA, VGA |
| Sound Output | One-piece, 1-watt Mono |
| Voltage | 100-240V AC; 50/60/Hz (auto sense/select) |
| BTU Rating | 1024 BTU |
| dB Rating | N/A |
| Power Consumption | 300W |
| Dimensions (WxHxD) | 13.1" x 3.5" x 10.0" |
| Net Weight | 9.3 lbs. |
| User Maintenance | Clean air filters, replace lamp assembly |
| PC Input Terminals | DVI-I (w/ D-Sub15 adapter) Audio Mini-jack (stereo) |
| Video Input Terminal | Component RCA x 3 (Y/Video, Pb/Cb, Pr/Cr) S-Video (mini-DIN 4-pin) Audio RCA x 2 (R, L-mono) |
| Output Terminal | D-Sub15 • Audio RCA x 2 (R, L-mono) |
| Control Port Terminal | Mini DIN 8-pin • USB type B |
| Included Accessories | I/R remote control with mouse pad and Laser Pointer • 2 AA batteries • Owner's manual • VGA computer cable • PS/2 control cable • Video cable (RCA) • Audio cable (RCAx2) • DVI-I/D-Sub15 adapter • Lens cap • Soft carry bag • AC power supply cord |
| Optional Accessories | • Wireless Imager Kit - includes Imager Module, Wireless LAN Card, software CD-ROM, Owners Manual (POA-WL11) • Media Card Imager Kit - includes Detachable Presentation Viewer, MCI CD-ROM software, 16MB Compact Flash Card, PC-Card adapter, Owner's Manual (POA-MD07MCI) • Serial Control Cable (POA-MCSRL) • ADB Control Cable (POA-MCMAC) • MAC/VGA adapter (POA-MACAP) |
| Warranty | Three years parts and labor; 90 days lamp; Quick Repair Program under warranty |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Optional Wireless Imager (POA-WL11)
(Includes 1 wireless LAN card for projector)



Optional Presentation Viewer Kit
(POA-MD07MCI)



Input / Output Terminals