NEW MODELS
Sept 2004

SANYO

Wireless Ultra Portable LCD projectors

PLC-XU51

- **XGA resolution**
- **2000 ANSI lumens**
- **Optional multi-card imager box –** Wired/ Wireless LAN / Viewer Capability
- **Auto Set Up –** Vertical Keystone & PC Adjust
- **Monitor output –** Switchable 2nd Data Input
- **Manual zoom**
- **PIN Code Security**
- **Remote control with laser pointer**
- **Short-throw flex lens 1.25-1.95:1**
- **Weighs only 2.8kg**

Model name	PLC-XU51
Panel	0.79 inch TFT p-Si x 3
No. of pixels	1024 x 768
Projection lamp	200W UHP / 150W Eco Mode
Brightness (typical)	2000 ANSI lumens
Uniformity	85% (corner to centre)
Contrast ratio	450:1
Up-Down ratio	9:1, Digital Keystone ± 40° vertical, ± 20° horizontal
Projection lens Throw ratio Screen size	F 1.7 - 2.5, f=20 – 30mm 1.25 – 1.95:1 40”-300”
AV Signal	Input: Composite (RCA), Component(D-Sub15), S-Video(DIN4) Stereo (RCAx2)
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
PC Signal	Input: DVI-I x 1 (Digital/Analogue) Audio input: Stereo x 1 (mini jack) Audio output: Stereo x 1 (mini jack) Output: RGB (D-Sub15), switchable 2nd data input
Control Port	Serial x 1 (Mini DIN8-pin), USB type B x 1
Computer compatibility	SXGA/XGA/SVGA/VGA/MAC
Scanning frequency	H sync ~100kHz, V Sync ~100Hz Dot clock 140 MHz
Sound output	1.0W mono
Voltage	100V-240V AC (auto voltage)
Dimensions(W x H x D)	298 x 71 x 218 mm
Weight	2.8kg