

SIM2 *Grand Cinema*TM HT380

Exceptional home theater



Key points

- 1080p 0,95" DLP® chipset
by Texas Instruments
- 1920 x 1080 pixel HDTV resolution
- Proprietary SIM2 Alphapath™ light engine
- Full BrilliantColor™ technology with primary and secondary colors segment colour wheel
- New Unishape technology
- Lamp: 160W
- Contrast ratio >5000:1
- 1 HDMI™ HDCP inputs
- NEW SIM2 Live Colors Management and Gamma Functions

SIM2's Grand Cinema™ series is regarded as the pinnacle of technical excellence in home theater projector design. Each model offers class-leading performance, along with a design elegance typical of products with an Italian pedigree.

Grand Cinema™ HT380 is the latest addition to this legendary series; this compact Full HD model uses leading-edge technology in its design to create a projector with true high-end performance. Texas Instruments' next generation 0,95" 1080p DLP® (1920 x 1080 pixel resolution) chipset is integrated into SIM2's patented ALPHAPATH™ light engine and it is this partnership of precision optics and fine pixel detail that offers a level of picture clarity that is truly exceptional.

HT380 is yet another world's first for SIM2. It features two new technologies, namely: BrilliantColor™ and Unishape™ lamp technology. These two enhancements combine to improve HT380's picture performance by increasing its light output and contrast ratio, whilst offering a much wider color palette than conventional designs.

Designed to be the perfect partner for HDTV, Blu Ray and HD DVD, HT380 also enables even standard definition sources to be reproduced at 1080p resolution, thanks to its sophisticated on-board 10-bit video processing electronics. Compatible with all video and graphics standards (including 1080p@24fps), HT380 offers a wide choice of both analog and digital source inputs, including HDCP compliant HDMI™.

The Grand Cinema™ HT380 projector is available in an elegant Gun Metal gloss finish cabinet.



SIM2 *Grand Cinema*TM HT380

Technical Specifications



LIGHT ENGINE

Technology: 1 chip DMD 0,95" 1080p DarkChip3TM
 Resolution: 1920 x 1080 pixels
 Full BrilliantColorTM technology and new color wheel
 (with primary and secondary colors)
 Lamp power & life time*: 160W, 4000 hours*

INSTALLATION

Throw ratio: 1,5-2,0(standard); 2-3,0:1 (optional)
 Lens shift: V+/-6°
 Digital keystone adjustment: V+/-18°
 Picture size (inches diagonal): 50-300
 Aspect ratio: 4:3, 16:9 Anamorphic, LetterBox,
 panoramic, pixel to pixel, 3 custom-user adjustments

ELECTRONICS

Horizontal & vertical scan freq.: 15-80kHz/24-100Hz
 Video and Graphic standards: PAL (B,G,H,I,M,N,60);
 SECAM; NTSC 3,58; NTSC 4,43 automatically
 selected; HDTV: ATSC (480p, 720p, 1080i, 1080p);
 EU 576p + 1080i 50Hz; PC graphic: VGA, SVGA,
 XGA, SXGA, UXGA
 Contrast ratio (Full ON/ Full OFF): >5000:1
 Format Board and video processor: 10 Bit built in
 Special video adjustments: Dynamic Noise
 Reduction, Spatial Noise Reduction, Fleshtone
 Regulation
 Other special adjustments: Memories/Overscan, Live
 Colors Management (LCM) and Gamma Functions;
 Full BrilliantColorTM and UnishapeTM technology

INPUTS/OUTPUTS

1 x Composite Video (RCA)
 1x S-Video (mini Din 4 pin)
 1 x RGBS/YCrCb (4x RCA)
 1 x RGBHV/YCrCb (1x VGA)
 1 x HDMI – HDCP compliant
 1 x OUT Digital Audio (Toslink)
 1 x RS232 (D-Sub 9 pin)
 1 x Input External IR sensor
 2 x OUT 12V 100mA (via Jack)

GENERAL SPECIFICATIONS

Software control: upgradable via RS232 serial
 interface
 Mains voltage range: 100-240Vac ±10% (48/62Hz)
 Weight: 5.8Kg (12.8 lbs)
 Dimensions (WxHxD): 350x173x318 mm
 (13.8"x6.8"x12.5")

SUPPLIED ACCESSORIES

Installation and User Manual; AC power cords (EU,
 UK and USA) 2m (6.6 ft); Backlit remote control and
 batteries

The DLP® logo and DLP® medallion are trademarks of Texas Instruments.

(*) Lamp life: the hours quoted have been measured in a lab under strict test conditions. Lamp life varies depending on usage conditions and the surrounding environment. The measured lamp life cannot be guaranteed and is not protected by warranty

Due to constant product development, specifications and design might be subject to change without notice. HT380, June 2007

Headquarters:
 SIM2 MULTIMEDIA S.p.A.
 Viale Lino Zanussi, 11
 33170 Pordenone - Italy
 Tel. +39.0434.383234
 Telefax +39.0434.383260
 E-mail: info@sim2.it

Germany
 SIM2 DEUTSCHLAND GmbH
 ArndtStr. 34-36
 D-60325 Frankfurt Am Main
 Tel. 0800.8007462 (Germany only)
 Int. tel. +49-163-500 7462
 E-mail: info@sim2.de

UK:
 SIM2 UK LTD
 Steinway House, Worth Farm
 Little Horsted, Nr. Uckfield
 East Sussex TN22 5TT
 Tel. +44.01825.750850
 E-mail: info@sim2.co.uk

USA:
 SIM2 USA INC.
 10108 USA Today Way
 Miramar, FL 33025
 Tel. +1.954.442.2999
 Telefax +1.954.442.2998
 E-mail: sales@sim2usa.com

