Sonnoc SNP-LU75KC





























Brief Introduction Beta 2.5

Display Type

Ansi-Lumen

Contrast Black Level Lens shift

Resolution

Video Modes 3D Compatibility

Application

Light Source Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

2 x 10W Audio



A brief introduction to the SNP-LU75KC: The Sonnoc Stationary 3D Laser DLP projector offers 7700 ANSI lumens, a contrast of 3000000:1 and a WUXGA 1920 x 1200 resolution. The manufacturer specifies a laser lifespan of 200,000 hours, which would be 13.7 years with 4 hours of viewing per day. The built-in lens shift and keystone correction function provides freedom when adjusting the projection. The projector can illuminate up to 892 cm of image width well with its 7700 ANSI lumens. The projector can handle rooms with low light, but we would recommend a smaller image width for rooms with more light. Furthermore, the projector can play 1080P and 4K (compressed) as well as 3D without any problems, and thus all currently available Blu-ray formats can be recognized by the projector. With only 30 decibels of operating noise, the model is already very quiet compared to others.

ω3422 Lux (bei 200 cm Screen)

ត្តិ 3000000:1 [©] 0,001 min. Lumen

1 x 0,67" DMD DLP Chip

WUXGA 16/9 Ti Digital Light Processing Chip

7700 3000000:1

0,0026 min. Lumen

Vert.: +/-100% Hori.: +/-30% WUXGA 1920 x 1200

2.304.000 Pixel

UHD (4K2K) 3840 x 2160 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD (komprimiert), 3D, EDTV 480p, 576p

Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom

Frame Sequential (3D Ready)

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Very large screen width and rooms with plenty of light and shaded daylight.

MCL Laser Diode

20000 h. Normal / 25000 h. Eco

0,00 € Laser

Powered

Powered 1,26

optional

optional



HDMI 2.0 in

2x HDMI 2.0 (HDCP) 3D Sync in und out Mini Jack Audio out

Connections USB-A in

RS232C Din 9 pin in Wired Remote 3,5mm

RJ45 in HDBaseT

Ceiling Mounting

Yes

Power 405W

Size WxHxD 486 x 181 x 376 mm (19,1"x7,1"x14,8") 33,08 L/dm³

Operating Noise 30 / 25 dB in Eco Mode

Weight 11,50 kg / 24,25 lbs.

Keystone Vert.: +/-40° Hori.: +/-30°

Illumination 90%

Frequenz -

Foot-Lamberts 318 fL / max. 892 cm screen width

1090 cd/m²

Real Full HD 3D

■ Full HD 1080P compatible

Lens shift Funktion

■ Eco Mode

■ High Dynamic Range (HDR)

Features Warping

■ 360° installable

■ 24/7 continuous operation capable

Optional Wi-Fi network compatible.

Lan network compatible.

■ Color Management System

Optionaler Zubehör



Deckenhalterung Länge 225 mm

Halterung45

Shift: 60 cm

Shift: 113 cm

Shift: 113 cm

Shift: 60 cm

85,80€

Optional Lenses

Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
Standard 1.2-1.5	1.2-1.5:1	2.4-3 m			Powered
Standard 0.7-1.2	0.7-1.2:1	1.4-2.4 m			Powered
Optional 2.90-5.50	2.9-5.5:1	5.8-11 m			Powered
Optional 1.52-2.92	1.52-2.92:1	3-5.8 m			Powered
Optional 0.65-0.75	0.65-0.75:1	1.3-1.5 m			Powered
Fix Optional Lenses					
Standard 0.55	0.55:1	1.1 m			No Zoom
Status	2024 Current model // Last update of the data: 2024-11-15				

Data









More Details



HCinema

https://www.projector-database.com/pro/sonnocsnplu75kc-en.html