

VDC Marquee 8110+



Display Type	 8" EMF CRT UXGA 4/3 Elektromagnetisch Fokussierte Röhre
Ansi-Lumen	-
Contrast	-
Black Level	-
Offset	-
Resolution	UXGA 1600 x 1200 1.920.000 Pixel
Video Modes	-
Application	CRT Projection Very narrow picture width and rooms with very little light.
Light Source	CRT Röhre
Light Life	ca. 10000 - 20000 h. (je nach Anwendung)
Operating Costs	-
Focus	-
Zoom	-
Objective	HD8
Throw Ratio	-
Audio	-
Connections	-
Ceiling Mounting	Yes
Power	-
Size WxHxD	710 x 420 x 810 mm (28"x16,5"x31,9") 241,54 L/dm³
Operating Noise	-
Weight	65,00 kg / 143,3 lbs.
Keystone	-
Illumination	-
Frequenz	H-sync: 15-110 kHz V-sync: 38-180 Hz Range max.: 250 MHz
Foot-Lamberts	-

VDC MARQUEE 8110+

- Gamma correction
- Digital image shift
- Password protection
- Crestron®-Software compatible.

Features

Status - Discontinued (EOL) // Last update of the data: 2023-08-04

Data



More Details



HCinema

<https://www.projector-database.com/pro/vdcmarquee8110plus-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.