



2,000 Lumens



High Brightness



HDTV Ready



RGB Input x 2



Keystone Correction



Whisper Mode

Projector **PJ520**

> **Ideal for mobile professionals**

Versatile, portable, multimedia projector.

The ViewSonic PJ520 is the perfect union of form and function with 800x600 native resolution. It WEIGHS IN AT LESS THAN 6 POUNDS while its 2,000 LUMENS DELIVER ULTRA-BRIGHT, CRISP, CLEAR IMAGES. Unveil dynamic multimedia presentations in any setting. The multiple video inputs allow connectivity from different sources while one image can be output on an additional display. Rich in features and light on the wallet, the PJ520 is an excellent choice for business use.



Projector **PJ520**



PJ520



Model No:VS10141-1W

- **Native SVGA resolution**
Native SVGA(800 x 600)resolution compressing to UXGA(1600 x 1200)resolution.
- **Keystone Correction**
Techniques used in the projector to minimize the visible effect of keystone. Images are typically trapezoidal in shape and keystone correction is used to square the image.
- **Displays HDTV signals**
ViewSonic projectors project a wide variety of content including HDTV signals (480i, 480p, 575i, 720p, 1035i and 1080i).
- **Automatic source detection for easy setup**
Identify and project RGB and video inputs sources automatically. This is no need to switch source modes before projection.
- **Supports 4 : 3 and 16 : 9 aspect ratio**
Offering increased flexibility for multiple viewing formats.
- **Ultimate flexibility with multiple RGB inputs.**
Connect two computers simultaneously or add a video source for dynamic meetings.
- **Easy setup and auto tuning**
One-touch setup button for fast, easy sync and sharp focus.
- **Whisper-Mode**
Whisper-mode allows the user to operate the projector at two settings - "normal" for maximum performance and "whisper" for low noise levels plus extended lamp life.
- **Full-function wireless remote control**
The handy remote control is perfectly matching for mobile presentations. Plus the built-in presentation functions enable the versatility.
- **Digital Gamma Correction**
The 10-bit digital gamma correction circuits enable fine tonal expressions that cannot be reproduced by conventional technologies. Being able to reproduce fine differences in light and shade gives images a more 3D feel and permits a rich range of image expressions.
- **Best Service & Support**
At ViewSonic, we are devoted to customer satisfaction. We strive constantly to understand your interests and concerns, and treat you with respect, courtesy and consideration. For the warranty information, please contact your local ViewSonic distributor or ViewSonic service center.

LCD	Type	0.7" Poly-Silicon TFT active matrix LCD
	Resolution	SVGA 800x600
	Lens	Manual Zoom / Focus (1:1.2x)
DISPLAY	Size	30"- 300" (Diagonal)
	Throw Distance	0.9m-9.2m(2.9ft-30.2ft)
	Lamp	150W UHB,4,000 hours rating (Whisper - mode operating)
	Brightness	2,000 Lumens
	Contrast Ratio	300:1
	Keystone Correction	± 15°(V) , ± 5°(H)
	Aspect Ratio	4:3, 16:9
AUDIO	Speakers	1W x 1
INPUT SIGNAL	RGB	RGB analog
	Video	NTSC, PAL, SECAM
	HDTV	HDTV 480i,480p,575i,720p,1035i,1080i
	Frequency	Fh : 15-91kHz; Fv : 50-120Hz
COMPATIBILITY	PC	From VGA up to UXGA
	Mac [®]	Up to SXGA (may require Mac Adapter)
CONNECTOR	RGB Input	15-pin D-sub x2
	RGB Output	15-pin D-sub x1
	Composite Video	RCA x1
	Component Video	RCA x3
	S-Video	Mini-Din 4 pin x1
	Audio	RCA x2(R/L)
	Control	15 pin D-Sub x1
	USB	USB upstream x1
POWER	Voltage	90-132 VAC / 198-264 VAC, 50- 60Hz (Universal)
	Consumption	240W (typ)
USER CONTROLS	Basic	Standby On/Off, Menu (Left, Right, Up, Down), Input, Reset, Keystone, Indicators (Lamp, Power)
	Remote	Standby On/Off, Video, RGB, Menu, Position, Standby On/Off, Video, Laser, RGB, Menu, Position, Keystone, Arrow/Select(Left, Right, Up, Down), Enter, Escape, Reset, Magnify(On, Off), Freeze, Volume, Mute, Auto, Blank, Aspect, and Search Button, Disk Pad, Mouse
	OSD	Main: Brightness, Contrast, Aspect, Pict, Pos, Mirror, Language Picture-1: Color Bal R, Color Bal B, Sharpness, Color, Tint Picture-2: V-Position, H-Position, H-Phrase, H-Size Input: Auto(Execute), Video, HDTV, Sync On Green Screen: Blank, Start Up Option: Volume, Auto Off, Whisper, Lamp Time, Filter Time
OPERATING	Temperature	32°F to 95°F (0°C to 35°C)
CONDITION	Humidity	10% to 85% (non-condensing)
DIMENSIONS	Physical	295mm x 231mm x 76mm
(W X D X H)		
WEIGHT	Net	2.7kg (5.95 lbs)
REGULATIONS		UL60950/C-UL, FCCB, TUV/GS, CB, CE, C-Tick, TUV-S, NOM
WARRANTY		Three-year limited warranty on parts and labor One-year warranty on lamp

Specifications subject to change without notice.
Selection, offers, warranties and programs may vary by country; see your ViewSonic representative for complete details.

ViewSonic Service Center:

Taiwan service@tw.viewsonic.com
China service.cn@cn.viewsonic.com
Japan service@jp.viewsonic.com
S. Asia & S. E. Asia service@sg.viewsonic.com
Australia & New Zealand service@au.viewsonic.com
H.K service@hk.viewsonic.com
Korea service@kr.viewsonic.com
Other AP countries service@sd.viewsonic.com

Headquarters:

381 Brea Canyon Road, Walnut, CA91789, U.S.A.
Tel:(800)888-8583 (909)444-8888
Fax:(909)839-7922
E-mail:salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:

9F, No. 192 Lien Chien Road, Chung Ho, Taipei, R.O.C.
Tel:886-2-2246-3456
Fax:886-2-8242-3666
www.viewsonic.com.tw



ViewSonic
See the difference.®

(C) 2003 ViewSonic Corporation. all rights reserved.

www.viewsonic.com