

Key Features

Bright Images in any Environment | Energy-efficient

SuperEco | HDMI input and USB power | Network

Capable | SuperColor: Amazing Color Accuracy



Product Description

The ViewSonic® PG700WU projector features 3,500 lumens, 1920x1200 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. Equipped with Crestron® LAN controller, this projector makes it easy for IT admin to remotely control and manage multiple projectors from their workstations. With a shorter throw ratio, 1.2x optical zoom, vertical keystone, and extensive connectivity, the PG700WU provides flexible and quick set-up. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours*. The PG700WU is the ideal projector for both high definition presentations and vibrant multimedia entertainment.

*Lamp life may vary based on actual usage and other factors



1. IR remote sensor
2. Projection lens
3. Elevation foot
4. Focus / zoom rings
5. Monitor Out
6. VGA
7. USB type Mini B
8. HDMI (x2)
9. AC In

10. USB 2.0 Type A (powered)
11. RS232
12. Control Panel
13. Audio In
14. Kensington® Lock Slot
15. Audio Out



1920 x 1200
RESOLUTION



3,500 ANSI
LUMENS



1.5 - 1.7
THROW
RATIO

Contact Sales

call: 888.881.8781

email:

salesinfo@viewsonic.com

visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	WUXGA
Resolution:	1920 x 1200
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m

Throw Distance:	3.2 - 35.0 ft / 1.0 - 10.7 m
Throw Ratio:	1.5 - 1.7
Keystone:	Vertical ($\pm 40^\circ$)
Lens:	1.1x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	12,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1200
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1200
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(2), VGA In(1), VGA Out(1), Mini USB(1)

Audio:

Internal Speakers:	2W
--------------------	----

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	Copyright © 1ViewSonic Corporation 2000-2018. All rights reserved. (06/14/2018 12:13 PM PST)
-----------------------	--

Weight (imperial):

Net (lbs):	7.9
Gross (lbs):	10.8

Weight (metric):

Net (kg):	3.6
Gross (kg):	4.9

Dimensions (imperial) (WxHxD):

Packaging (in.):	14.4 x 7.4 x 11.8
Physical (in.):	13.1 x 5.3 x 10.3

Dimensions (metric) (WxHxD):

Packaging (mm):	336.0 x 207.0 x 417.0
Physical (mm):	332.0 x 135.0 x 261.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PG700WU projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907000733

Accessories:

HB10B, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PM-FCP, RLC-116, VC10, VCB10